

Tehnički list za artikl: BK080052-H

Uzidni razdj. za knauf, 2-redni, 24M , bijela vrata, IP40

355x282x106mm (VxŠxD), sadrži izolirane PE/N sabirnice (2x13 priključaka) i pokrove za prazna mjesta, klasa zaštite: II, nazivna struja: 63A, nazivni napon: 400V AC, materijal: ABS, ispitivanje na žarnu nit: 650°C, temperatura okoline: -25° do +60°C, bez halogena, prema: IEC 60670 / IEC 62208



SCHRACK-Info

- Flush-mounted domestic consumer unit enclosures in ABS with solid plastic doors
- Lock: push-button, a small cylinder can be installed
- Includes PE and N terminals
- Protection class II
- Halogen free according to RoHS
- Rated voltage 400VAC / In=63A
- Ambient temperature: -25° to +60°C
- Glow wire test: 850°C
- inclusive KNAUF Mounting Set
- Recess depth: 68-70mm
- Degree of protection: IP40, Impact resistance: IK08
- RAL9010 pure white



Tehnički podaci

Neto širina (mm)	282,00
Neto visina (mm)	355,00
Neto dubina (mm)	106,00
Neto masa (kg)	1,34
EAN	9004840969962
Disipacija snage (W)	-24,00
Min. temperatura okoline (°C)	-25
Maks. temperatura okoline (°C)	60
Materijal vrata	Plastika
Bezhalogena	Da
Izvedba/tip	Ugradni sa vratima
Broj redova	2
Modula u 1 redu	12
IP stupanj zaštite	IP40
Boja	RAL 9010 (čista bijela)

Tabela artikla

OPIS	KAT. BROJ
Uzidni razdj. za knauf, 2-redni, 24M , bijela vrata, IP40 355x282x106mm (VxŠxD), sadrži izolirane PE/N sabirnice (2x13 priključaka) i pokrove za prazna mjesta, klasa zaštite: II, nazivna struja: 63A, nazivni napon: 400V AC, materijal: ABS, ispitivanje na žarnu nit: 650°C, temperatura okoline: -25° do +60°C, bez halogena, prema: IEC 60670 / IEC 62208	BK080052-H
Dodatni pribor	
Polucilindar brava za razdjelnike BK0802..., metalna metal, 2x keys included	BK080096