


Tehnički list za artikl: BK0855053K

Okvir s vratima za 5-redni media-combi razdjelnik, 2xDIN šina

serija Gemini, metalni okvir s vratima BEZ UZIDNE KADE koja se (ako je potrebna) naručuje odvojeno: BK0850552A (uzdna kada za šuplji zid) ili BK0850052A (uzdna kada za puni zid), gornji dio ormarića opremljen s 2x DIN šina (24+4 modula), donji dio ormarića opremljen s 3x mrežasta montažna ploča, u isporuci i 1x šuko utičnica, WLAN proofed, IP30, RAL9003 (signalno bijela)



SCHRACK-Info

- Media combi-enclosures for partition wall or solid wall in two versions:
 - **Horizontal 3- to 5-rows** as well as
 - **Vertical 3- to 5-rows**
- **Horizontal designs:**
 - **BK0856032K** : 3x DIN-rails (36+6MW) and 3x mounting plates
 - **BK0856042K** : 4x DIN-rails (48+8MW) and 4x mounting plates
 - **BK0856052K** : 5x DIN-rails (60+10MW) and 5x mounting plates
- For completion, the following articles are necessary:
 - 1x Frame with door and insert (3-, 4- or 5-row)
 - 2x Wall boxes (3-, 4- or 5-row for solid wall or partition wall)
 - 1x Wall box brackets horizontal BK085098-A
- **Vertical designs:**
 - **BK0855032K** : 1x DIN-rail (12+2MW), 2x mounting plates and 1x built-in socket
 - **BK0855042K** : 2x DIN-rails (24+4MW), 2x mounting plates and 1x built-in socket

- **BK0855053K** : 2x DIN-rails (24+4MW), 3x mounting plates and 1x built-in socket
- **BK0855052K** : 3x DIN-rails (36+6MW), 2x mounting plates and 1x built-in socket
- For completion, the following articles are necessary:
 - 1x Frame with door and insert (3-, 4- or 5-row)
 - 1x Wall box (3-, 4- or 5-row for solid wall or partition wall)
- **General information** :
 - WLAN proofed
 - Frames and doors in coated sheet steel, all doors with door clip
 - Horizontal versions: Media door side with ventilation slots
 - Vertical versions: Door with ventilation slots as standard
 - Frame design high (ca. 6 mm)
 - Mounting plates for active and passive components included
 - Glow wire test:
 - Resistant to abnormal heat and fire up to 850 °C for partition wall
 - Resistant to abnormal heat and fire up to 650 °C for solid wall
 - Mounting brackets (included):
 - For partition wall (up to 30 mm wall thickness)
 - For solid wall (Dovetail mounting brackets for front or back panel mounting)
 - Protection class: II
 - Degree of protection: IP30
 - Impact Resistance: IK08
 - Color: RAL9003 (Signal white)



Tehnički podaci

Neto širina (mm)	346,00
Neto visina (mm)	842,00
Neto dubina (mm)	36,00
Neto masa (kg)	5,00
EAN	9004840977790
Disipacija snage (W)	-61,00
Min. temperatura okoline (°C)	-25
Maks. temperatura okoline (°C)	60
Bezhalogena	Da
IP stupanj zaštite	IP30
Klasa zaštite	2
Udarna čvrstoća	IK08

Tabela artikla

OPIS	NVP (%)	MASA BAKRA (kg/km)	KAT. BROJ
Okvir s vratima za 5-redni media-combi razdjelnik, 2xDIN šina serija Gemini, metalni okvir s vratima BEZ UZIDNE KADE koja se (ako je potrebna) naručuje odvojeno: BK0850552A (uzdna kada za šuplji zid) ili BK0850052A (uzdna kada za puni zid), gornji dio ormarića opremljen s 2x DIN šina (24+4 modula), donji dio ormarića opremljen s 3x mrežasta montažna ploča, u isporuci i 1x šuko utičnica, WLAN proofed, IP30, RAL9003 (signalno bijela)			BK0855053K
Potrebni pribor			
Uzidna kada za 5-redni razdjelnik, montaža u šuplji zid 817x324x87mm (VxŠxD), 60+10 modula, za 5-redne BK085... razdjelnike, BK0857... media razdjelnike, BK0855... media combi razdjelnike (vertikalno), materijal kade: samogasivi ABS, ispitivanje na žarnu nit do 850°C			BK0850552A
Uzidna kada za 5-redni razdjelnik, montaža u puni zid 817x324x87mm (VxŠxD), za 5-redne BK085 uzidne razdjelnike, BK0857 media razdjelnike i BK0855 media combi-razdjelnike (vertikalno), materijal kade: ABS, ispitivanje na žarnu nit do 650°C			BK0850052A
Dodatni pribor			
Dvostruka šuko utičnica s montažnim nosačem 16A, 250V AC za BK0857... Uzidne media razdjelnike, BK0855... media-combi razdjelnike (vertikalno) i BK0856... media-combi razdjelnike (horizontalno) i BK0807... nazidne media razdjelnike			BK085050
Nosač uređaja (npr. routera) za media razdjelnike BK08... BK0855... media-combi razdjelnike (vertikalno) i BK0856... media-combi razdjelnike (horizontalno), za BK0857... uzidne media razdjelnike, i BK0807... nazidne media razdjelnike			BK085094-A
Set za vertikalno povezivanje svih BK085... razdjelnika set=2 komada, za vertikalno povezivanje uzidnih kada serije BK085, materijal: ABS			BK085095
DIN profil za montažu uređaja s većom ugradnom dubinom za uređaje s većom ugradnom dubinom (npr. odvodnike prenapona), za BK0857 media razdjelnike, BK0855 media combi-razdjelnike (vertikalno) i BK0856 media combi-razdjelnike (horizontalno)			BK085099
Metalna brava 2233X za razdjelnike BK085 i Media BK0807 brava se isporučuje u kompletu s jednim ključem			BK085097
Rezervni ključ za bravu BK085097-- (za razdjelnike BK085...) ključ za bravu 2233X (metalni), za razdjelnike BK085			BK085093
Rezervni dijelovi za BK085 seriju ormara (za okvire i vrata) set sadrži: 1x bravica vrata, 2x šarke vrata, 1x set za fiksiranje okvira u 6 točaka, 2x vijci prednjeg pokrova za uređaje			BK085090
Rezervni dijelovi za BK085 seriju ormara (za okvire i vrata) sadrži: 4x sidrište za montažu u šuplji zid, 4x kutnik za montažu u puni zid			BK085091

Tabela artikla

OPIS	NVP (%)	MASA BAKRA (kg/km)	KAT. BROJ
Dodatni pribor			
Adapter za DIN profil, prazan, za 1 modul (SFA)(SFB) Svjetlo siva			HSERH010GS
TOOLLESS LINE modul RJ45 oklop., cat.6a 10GB, 4PPoE 100W SFA (SFA)			HSEMRJ6GWA
S/FTP inst. kabel cat.7,4x2xAWG23/1,1000MHz,LS0H-3,Cca,50% s 1a,d1,a1, plavi, za rezanje	79	28	HSEKP423CB
Šuko utičnica jednostruka, za media ormariće serije Gemini za dodatnu ugradnju u BK0855 media combi-razdjelnike (vertikalno)			BK085049