


Tehnički list za artikl: BKUP401GA-

UP-Wohnungsverteiler 3-reihig mit FI "G", Typ "A"

Bestückt und verdrahtet - IP40, Schutzklasse II, 36+6 TE, Vorsicherung max. 25A, LS-FI-Schalter Kennl.B, 16A, FI-GA, C16/3+N, 4xB13 1+N, 2xB16 1+N, RAL9003 Signalweiß, Breite=346mm, Höhe=592mm, Tiefe=96mm



Tehnički podaci

Neto širina (mm)	346,00
Neto visina (mm)	592,00
Neto dubina (mm)	96,00
Neto masa (kg)	5,90
EAN	9004840870862
Disipacija snage (W)	-80,50
Izvedba/tip	Uzidni, za šuplje stijene, s vratima
Materijal vrata	Čelik
Modula u 1 redu	12+2
IP stupanj zaštite	IP40
Boja	RAL 9003 (signalno bijela)
ŠxVxD mm	346x592x96

Tabela artikla

OPIS	KAT. BROJ
UP-Wohnungsverteiler 3-reihig mit FI "G", Typ "A"	
Bestückt und verdrahtet - IP40, Schutzklasse II, 36+6 TE, Vorsicherung max. 25A, LS-FI-Schalter Kennl.B, 16A, FI-GA, C16/3+N, BKUP401GA	
4x B13 1+N, 2x B16 1+N, RAL9003 Signalweiß, Breite=346mm, Höhe=592mm, Tiefe=96mm	