

Tehnički list za artikl: DT478080-B

Samostojeći kom. ormar DT Š800xV2010xD800, 19", 47U, crni RAL9005



SCHRACK-Info

The S-RACK 19" freestanding network enclosure is the perfect solution for offices and similar environments. It is suitable for use as a central enclosure in network installations, but also as a sub-enclosure in the horizontal area of a structured cabling system.

The removable side and rear panels allow comfortable and easy access from all sides.

Cooling of the built-in components is achieved passively by heat exchange with the outside area and actively by optional roof fans.

Cable entry is very flexible due to various prepared opening possibilities or the optional base.

The S-RACK enclosures are designed for universal use and cover the widest possible range of applications.

- **Material thickness:**

- Top and bottom chassis: 1.5mm
- Corner profile: 1.2mm
- Rails: 1.5mm
- Front door (glass): 4.0mm
- Rear panel: 0.8mm
- Side panel: 0.8mm

- **Colours:**

- RAL9005 (black)
- Strips: RAL5005 (signal blue)

- **Height:** 47U

- **Width:** 800mm

- **Depth:** 800mm

- **Maximum load:** with even distribution: 800kg
- **Degree of protection:** IP20
- **Dismountability:** The individual parts of the cabinet are screwed. The enclosure is delivered assembled and can be partially or completely disassembled for transport to places that are difficult to access.
- **Doors:** Glass door including comfort swing handle with lock and keys. A conversion kit for half cylinders (DTZLOCK02) is optionally available. External hinge system allows door opening angle of up to 180°. Door hinged on the right. Conversion to left hinged door is possible. Glass door can be replaced by optionally available doors DTRT (full metal or perforated, full width or double door).
- **Side and back panels:** Removable side and back panels with lock and keys. Rear wall can be replaced by optionally available doors DTRT (glass, full metal or perforated, full width or double door).
- **Cable entry options:** In roof and floor. Fitted with plastic blank covers. The floor also accommodates a large break-out blank plate which can be easily removed for cable entry. Brush entry DTBB optionally available.
- **Cooling:** Passive cooling through heat exchange with the outside area. Ventilation slots on the roof are prepared for cooling. Active cooling through optional DTLT fan units.
- **Rails:** 19" rails (4 pieces), depth adjustable, U markings included
- **Accessories:** Numerous accessories (base sets, fans, shelves, cable management, doors, etc.) available
- **Earthing:** Earthing set is included
- **Levelling Feet:** Levelling Feet are included
- **Included mounting material:** 16 pieces cage nuts, screws and washers
- **Delivery:** Enclosure is delivered fully assembled on a throw-away pallet.



Tehnički podaci

Neto širina (mm)	800,00
Neto visina (mm)	2.232,00
Neto dubina (mm)	800,00
Neto masa (kg)	94,60
EAN	9004840889802
Min. temperatura okoline (°C)	5
Maks. temperatura okoline (°C)	40
Visinska jedinica	47
Boja	RAL 9005 (crna)
IP stupanj zaštite	IP20
Maksimalno opterećenje (kg)	800
Serijski broj	S-RACK

Tabela artikla

OPIS	KAT. BROJ
Samostojeći kom. ormar DT Š800xV2010xD800, 19", 47U, crni RAL9005	DT478080-B
Dodatni pribor	
Podnožje v=100, komplet za DT ormare š=800 x d=800, RAL9005 crno	DTOT10808B
Krovna vent. jed., 2 vent. za DT/DTW, analog. term., RAL9005 Installation from outside of enclosure, for freestanding and wallmount enclosures	DTLTRO2A-B
Krovna vent. jed., 4 vent. za DT/DTW, digit. term., RAL9005 RAL9005, Installation from inside of enclosure. Suitable for 800, 1000 and 1200mm deep enclosures. Not recommended for 600mm deep enclosures.	DTLTRO4D-B
Krovna vent. jed., 4 vent. za DT/DTW, analog. term., RAL9005 RAL9005, Installation from inside of enclosure	DTLTRO4A-B
Četka za uvod kabela, strop/pod S-RACK samostojećih ormara 70x316mm, mjenja dva slijepa panela	DTZBRUSH02
Četka za uvod kabela, strop/pod S-RACK samostojećih ormara 70x500mm, mjenja tri slijepa panela	DTZBRUSH03
Adapter zakretne ručke za polucilindar S-RACK s. ormara Samostojeći ormari	DTZLOCK02
Set za rednu ugradnju DT kom. ormara, D=800 i 1000mm, RAL9005 1 set = 2 pokrova (za vrh i dno) + 8x vijaka 6.3 x 12	DTRA0800-B
19" fiksna polica do 50kg, dubine 570mm, 1U, RAL9005 učvršćenje u 4 točke	DTFF1570-B
19" fiksna polica do 50kg, dubine 450mm, 1U, niskoprofilna učvršćenje u 4 točke, RAL9005	DTFL1450-B
19" vodilica kabela s 5 metalnih prstena, 1U, RAL9005	DTBC105R-B
19" vodilica kabela s 5 metalnih prstena 130mm, 1U, RAL9005	DTBC105RGB
19" set vijaka, kaveznih matica+podložne pločice M6 (50 kom)	DTSRA050
LED rasvjeta za ormare, magnet, 230VAC, s kontaktom za vrata automatski u radu čim se otvore vrata, vanjsko napajanje	DTLIGHT01
Set okomitih vodilica kabela za DT ormare, metalni, 47U 1 pak. = 2 kom, crni RAL9005	DTKV47MS-B
19" set za uzemljenje za S-RACK ormare, 1U, 10 priklj. točaka 4 x 4mm x 40cm žuto/zeleni vodič, s vijcima i maticama	DTRE0001
Prespojni panel 19", prazan, za 24 modula, 1U, crni, ECO svjetlo siva, jezičac prespojnog kabela okrenut prema dolje	HSER0240SP
19" napojna letva s 9xšuko, alu 1U, kabel 3m, RAL7035	IU070114-3
19" napojna letva sa 7xšuko+prenaponska zaštita, 1.25U kabel s utikačem 2m, RAL7035	IU070113

Tabela artikla

OPIS	KAT. BROJ
Dodatni pribor	
19" Napojna letva, 9xšuko+prekidač 1U, kabel 2m, crna, alu ALU profil	Q7070114-A
19" Napojna letva, 7xšuko+prekidač, prenap.zaštita, crna 1U, kabel 2m, alu profil, crna	Q7070113-A
Preklopnik 24xRJ45 10/100/1000T, bez vent., unut. napajanje Metalno kućište, 19"	QLGSW2457