

Tehnički list za artikl: DTS478080-

Serverski samost. ormari 19" 47U, IP20, 800x2176x800 ŠxVxD

crni RAL9005, nosivost 1000 kg



SCHRACK-Info

Server cabinets are mainly used in data centers and server rooms where an increased load is required and heavy installations such as servers, UPS, etc., have to be installed.

The maximum load is 1000kg.

Front door: Perforated (70%) metal door arched.

Rear door: Perforated (70%), split metal door arched.

The side panels of the server cabinet can be removed and allows easy access to all installations from all sides.

The server cabinet is cooled both actively and passively.

The cooling works passively via perforated doors and actively via roof fans.

The 19" server cabinet from Schrack Technique ensures a high level of flexibility in cable entry due to the prepared opening option in the upper area.

TECHNICAL DATA

- Colour: RAL9005 black
- The opening angle of the front door is up to 230°C
- Height: 47U
- Width: 800mm
- Depth: 800mm
- Degree of protection: IP20
- Maximum load: 1000kg


- Doors: Rear doors are in standard 70% perforated, double door with 3 point locking system. Front door monoblock 70% perforated, arched metal door with 4 point locking system and swing handle lock, RAL9005 black.
- The side panels are lockable and removable with a cylinder lock
- Fan: Installation is from the roof, no interference with installed equipment or cables inside the cabinet.
- Cable entry option: In the top cover with sliding rubber edge.
- Structure of the enclosure: 19" rails are bent 4-times for reasons of strength. 2.0mm thickness ensure high resilience. The 19" rails are made of steel with an 8 – 12 micron zinc coating for corrosions resistance.



Tehnički podaci


Neto širina (mm)	800,00
Neto visina (mm)	2.176,00
Neto dubina (mm)	800,00
Neto masa (kg)	120,53
EAN	9004840895407
Min. temperatura okoline (°C)	5
Maks. temperatura okoline (°C)	40
Visinska jedinica	47
Boja	RAL 9005 (crna)
IP stupanj zaštite	IP20

Mjerne skice: Serverski samost. ormari 19" 47U, IP20, 800x2176x800 ŠxVxD




BOTTOM VIEW


Mjerne skice: Serverski samost. ormari 19" 47U, IP20, 800x2176x800 ŠxVxD



FRONT VIEW




SIDE VIEW




REAR VIEW

Mjerne skice: Serverski samost. ormari 19" 47U, IP20, 800x2176x800 ŠxVxD



TOP VIEW

Mjerne skice: Serverski samost. ormari 19" 47U, IP20, 800x2176x800 ŠxVxD

OPIS

Serverski samost. ormari 19" 47U, IP20, 800x2176x800 ŠxVxD
crni RAL9005, nosivost 1000 kg

KAT. BROJ

DTS478080