


Tehnički list za artikl: DTT478080B

Serverski ormar S-RACK, Š800 V2232 D800, 19", 47U

800kg nosivost, prednja vrata perforirana jednostruka, zadnja vrata perforirana dvostruka, RAL9005 crni



SCHRACK-Info

Server cabinets are mainly used in data centers and server rooms where an increased load is required and heavy installations such as servers, UPS, etc., have to be installed.

- **Material thickness:**
 - Top and bottom chassis: 1.5mm
 - Corner profile: 1.2mm
 - Rails: 1.5mm
 - Front metal door perforated, full width: 80%
 - Rear door perforated double-wing: 80%
 - Side panel: 0.8mm
- **Colour:**
 - RAL9005 (black)
- **Height:** 47U
- **Width:** 800mm
- **Depth:** 800mm
- **Maximum load:** with even distribution: 800kg
- **Degree of protection:** IP20

- **Dismountability:** The individual parts of the cabinet are screwed. The enclosure is delivered assembled and can be partially or completely disassembled for transport to places that are difficult to access.
- **Frontdoor:** Metal door perforated full width including comfort swing handle with lock and keys. A conversion kit for half cylinders (DTZLOCK02) is optionally available. External hinge system allows door opening angle of up to 180°. Door hinged on the right. Conversion to left hinged door is possible.
- **Side and back doors:** Removable side and back doors with lock and keys.
- **Cable entry options:** In roof and floor. Fitted with plastic blank covers. The floor also accommodates a large break-out blank plate which can be easily removed for cable entry. Brush entry DTBB optionally available.
- **Cooling:** Passive cooling through heat exchange with the outside area. Ventilation slots on the roof are prepared for cooling. Active cooling through optional DTLT fan units.
- **Rails:** 19" rails (4 pieces), depth adjustable, U markings included
- **Accessories:** Numerous accessories (base sets, fans, shelves, cable management, doors, etc.) available
- **Earthing:** Earthing set is included
- **Levelling Feet:** Levelling Feet are included
- **Included mounting material:** 16 pieces cage nuts, screws and washers
- **Delivery:** Enclosure is delivered fully assembled on a throw-away pallet.

Tehnički podaci

Neto širina (mm)	800,00
Neto visina (mm)	2.232,00
Neto dubina (mm)	800,00
Neto masa (kg)	96,60
EAN	9004840888348
Min. temperatura okoline (°C)	5
Maks. temperatura okoline (°C)	40
Visinska jedinica	47
Boja	RAL 9005 (crna)
IP stupanj zaštite	IP20
Maksimalno opterećenje (kg)	800
Serijski broj	S-RACK

Tabela artikla

OPIS	KAT. BROJ
Serverski ormar S-RACK, Š800 V2232 D800, 19", 47U	DTT478080B
800kg nosivost, prednja vrata perforirana jednostruka, zadnja vrata perforirana dvostruka, RAL9005 crni	
Dodatni pribor	
Podnožje v=100, komplet za DT ormare š=800 x d=800, RAL9005 crno	DTOT10808B

Tabela artikla

OPIS	KAT. BROJ
Dodatni pribor	
Krovna vent. jed., 2 vent. za DT/DTW, analog. term., RAL9005 Installation from outside of enclosure, for freestanding and wallmount enclosures	DTLTRO2A-B
Krovna vent. jed., 4 vent. za DT/DTW, digit. term., RAL9005 RAL9005, Installation from inside of enclosure. Suitable for 800, 1000 and 1200mm deep enclosures. Not recommended for 600mm deep enclosures.	DTLTRO4D-B
Krovna vent. jed., 4 vent. za DT/DTW, analog. term., RAL9005 RAL9005, Installation from inside of enclosure	DTLTRO4A-B
Četka za uvod kabela, strop/pod S-RACK samostojećih ormara 70x316mm, mjenja dva slijepa panela	DTZBRUSH02
Četka za uvod kabela, strop/pod S-RACK samostojećih ormara 70x500mm, mjenja tri slijepa panela	DTZBRUSH03
Adapter zakretne ručke za polucilindar S-RACK s. ormara Samostojeći ormari	DTZLOCK02
Set za rednu ugradnju DT kom. ormara, D=800 i 1000mm, RAL9005 1 set = 2 pokrova (za vrh i dno) + 8x vijaka 6.3 x 12	DTRA0800-B
19" fiksna polica do 50kg, dubine 570mm, 1U, RAL9005 učvršćenje u 4 točke	DTFF1570-B
19" fiksna polica do 50kg, dubine 450mm, 1U, niskoprofilna učvršćenje u 4 točke, RAL9005	DTFL1450-B
19" vodilica kabela s 5 metalnih prstena, 1U, RAL9005	DTBC105R-B
19" vodilica kabela s 5 metalnih prstena 130mm, 1U, RAL9005	DTBC105RGB
19" set vijaka, kavezni matica+podložne pločice M6 (50 kom)	DTSRA050
LED rasvjeta za ormare, magnet, 230VAC, s kontaktom za vrata automatski u radu čim se otvore vrata, vanjsko napajanje	DTLIGHT01
Set okomitih vodilica kabela za DT ormare, metalni, 47U 1 pak. = 2 kom, crni RAL9005	DTKV47MS-B
19" set za uzemljenje za S-RACK ormare, 1U, 10 priklj. točaka 4 x 4mm x 40cm žuto/zeleni vodič, s vijcima i maticama	DTRE0001
Prespojni panel 19", prazan, za 24 modula, 1U, crni, ECO svjetlo siva, jezičac prespojnog kabela okrenut prema dolje	HSER0240SP
19" napojna letva s 9xšuko, alu 1U, kabel 3m, RAL7035	IU070114-3
19" napojna letva sa 7xšuko+prenaponska zaštita, 1.25U kabel s utikačem 2m, RAL7035	IU070113
19" Napojna letva, 9xšuko+prekidač 1U, kabel 2m, crna, alu ALU profil	Q7070114-A
19" Napojna letva, 7xšuko+prekidač, prenap.zaštita, crna 1U, kabel 2m, alu profil, crna	Q7070113-A

Tabela artikla

OPIS	KAT. BROJ
Dodatni pribor	
Preklopnik 24xRJ45 10/100/1000T, bez vent., unut. napajanje	QLGSW2457
Metalno kućište, 19"	