

Tehnički list za artikl: DTWE045445

Zidni komun. ormar S-RACK, Š540, V240, D450mm, 19", 4U

RAL7035 Light grey



SCHRACK info

Mainly used in offices and office-like environments, such as flats, single-family homes, etc. Suitable as a central distributor in small to medium-sized network installations, but also for use as a floor distributor (sub-distributor) in the horizontal area of structured cabling. The removable side panels allow convenient access to the installed components, even afterwards. For active cooling of the built-in components, optional DTLT fan units with one or two fans can be mounted in the roof.

- **Material:** Powder-coated steel sheet housing
- **Material thickness:**
 - Top and bottom chassis: 1.0mm
 - Corner profile: 1.0mm
 - Rails: 1.5mm
 - Front door (glass): 4.0mm
 - Rear panel: 1.0mm
 - Side panel: 0.8mm
- **Colour:**
 - RAL7035 (light grey)
 - Corner profile and rear panel: RAL5005 (signal blue)
- **Heights:** 4, 7, 9, 12 and 16U
- **Maximum load:** With even distribution: 80kg
- **Degree of protection:** IP20

- **Doors:** Glass door of safety glass 4mm including lock and 2 keys. Door hinged on the right. Conversion to left hinged possible. Opening angle of the door: approx. 200°.
- **Side panels:** removable and lockable
- **Rails:** 19" rails (2 pieces) in the front of the cabinet, galvanised, depth-adjustable
- **Cable entry options:** in roof and floor
 - The floor is provided with a plastic blank cover.
 - The roof is equipped with a brush entry.
- **Cooling:**
 - Passive cooling through ventilation slots and heat exchange with the outside area.
 - Active cooling by optional DTLT fans, which are easily and quickly inserted into the

Tehnički podaci

Neto širina (mm)	540,00
Neto visina (mm)	240,00
Neto dubina (mm)	450,00
Neto masa (kg)	9,40
EAN	9004840880700
Min. temperatura okoline (°C)	5
Maks. temperatura okoline (°C)	40
Visinska jedinica	4
Boja	RAL 7035 / RAL 5005 (svijetlo siva / plava)
IP stupanj zaštite	IP20
Maksimalno opterećenje (kg)	80
Serijski broj	S-RACK

Tabela artikla

OPIS	KAT. BROJ
Zidni komun. ormar S-RACK, Š540, V240, D450mm, 19", 4U RAL7035 Light grey	DTWE045445
Dodatni pribor	
Krovna vent. jedinica, 2 vent. za S-RACK, analog. termostatski RAL7035, instalacija s vanjske strane ormara	DTLTR02A
Krovna vent. jedinica, 2 ventilatora za S-RACK, s prekidačem RAL7035, instalacija s vanjske strane ormara	DTLTR02S
Krovna vent. jedinica, 1 vent. za S-RACK, analog. termostatski RAL7035, instalacija s vanjske strane ormara	DTLTR01A
Krovna vent. jedinica, 1 ventilator za S-RACK, s prekidačem RAL7035, instalacija s vanjske strane ormara	DTLTR01S

Tabela artikla

OPIS	KAT. BROJ
Dodatni pribor	
19" fiksna polica do 30kg, dubine 300mm, 1U, niskoprofilna učvršćenje u 2 točke, RAL7035	DTFT1300
Prespojni panel 19", prazan, za 24 modula (SFA)(SFB), 1U svjetlo siva, jezičac prespojnog kabela okrenut prema dolje	HSE0240GS
19" vodilica kabela s 5 metalnih prstena, 1U, RAL7035	DTBC105R
19" set vijaka, kaveznih matica+podložne pločice M6 (20 kom)	DTSRA020
Preklopnik 24xRJ45 10/100/1000T, bez vent., unut. napajanje Metalno kućište, 19"	QLGSW2457
19" napojna letva sa 9xšuko, alu 1U, kabel 2m, RAL7035	IU070114
19" napojna letva sa 7xšuko+prenaponska zaštita, 1.25U kabel s utikačem 2m, RAL7035	IU070113
19" Napojna letva, 9xšuko+prekidač 1U, kabel 2m, crna, alu ALU profil	Q7070114-A
19" Napojna letva, 7xšuko+prekidač, prenap.zaštita, crna 1U, kabel 2m, alu profil, crna	Q7070113-A