

Tehnički list za artikl: EV210026--

Tipkalo za upravljanje roletama, dvostruko, 10A, nazidno, IP54

na oprugu (utične priključne stezaljke)



SCHRACK info

Robust surface-mounted pushbutton made of durable and weather-resistant, glass-fibre-reinforced thermoplastic material equipped with an electrical interlock so that simultaneous actuation of the rockers only switches through one output. The switch is IP54 splash-proof and also provides additional protection against dust. Furthermore, it is resistant to chemicals and elevated temperatures and at the same time has a high impact strength (IK05). Inside the switch there is already a connected quick connection terminal for the earthing connection, which allows an even easier connection. Up to three cables can be routed through the sealing diaphragm both above and below the switch.



Tehnički podaci

Neto duljina (mm)	83,00
Neto širina (mm)	74,00
Neto visina (mm)	56,00
Neto masa (kg)	0,11
Serijski	VISIO IP54
Tip proizvoda	Sklopka
Radni napon AC (V)	230

Tehnički podaci - nastavak

Uklopna struja (AX)	10
Način ugradnje	AP
Način pričvršćenja	Vijak
IP stupanj zaštite	IP54
Boja	siva
Tip priključka	Utična stezaljka
Dopušteni kabeli	Kruti
Dopušteni presjek (mm ²)	1,5- 2,5
Materijal	ABS Bakar
Okoliš	bezhalogeno
Trajnost	ROHS
Ispitni znak	VDE
Dimenzije (mm)	83x74x56

Abmessungen (mm)




Tabela artikla

OPIS	KAT. BROJ
Tipkalo za upravljanje roletama, dvostruko, 10A, nazidno, IP54 na oprugu (utične priključne stezaljke)	EV210026
Dodatni pribor	
Adapter za vertikalno proširenje VISIO IP54 sklopki/utičnica	EV217002