

Tehnički list za artikl: H6USG07K0G

LED prespojni kabel RJ45 neoklopljen, cat.6, sivi, 7m



SCHRACK-Info

Patchcords for generic, structured network cabling systems. Support all applications requiring Class D to Class E (e.g. 1000Base-T, 100Base-TX, ATM) as well as VoIP, PoE. On the RJ45 connector of the LED patchcord, there are two contacts for the Patchfinder tool. By connecting the Patchfinder to the contacts, the boots at both ends of the LED patchcord start to light. Thus the patching is easily identified. During Light-functionality, Data-transmission remains stable and is not affected. Pin assignment 1:1.

Tehnički podaci

Kategorija	Cat.6
Sastav kabela	4x2xAWG24/7
Kabelski oklop	U/UTP
Konekcija	1:1
Brzina prijenosa	up to Gigabit Ethernet
Broj parica	4 + 1
Oklop	Neoklopljen
Vanjski omotač kabela	LSOH
LED funkcija	sa LED
Neto masa (kg)	0,02
Boja	siva

Tehnički podaci - nastavak

Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	50
RoHS	Konformno
Duljina prespojnog kabela (m)	7,0
Utikač - Norma	EN 60603-7
Tipovi utikača	RJ45 neoklopljen
Popunjenost	EIA/TIA 568B 1:1

Tabela artikla

OPIS	NVP (%)	MASA BAKRA (kg/km)	KAT. BROJ
LED prespojni kabel RJ45 neoklopljen, cat.6, sivi, 7m			H6USG07K0G
Dodatni pribor			
LED Detector Pro za LED prespojne kabla, CPZLWLA2 s ugrađenom punjivom baterijom i USB kabelom			HLEDTOOL1
Patchfinder izvor napajanja za LED prespojne kabele			HLEDTOOL
TOOLLESS LINE utični modul RJ45 cat.6, neoklopljen (SFA)			HSEMRJ6UWS
Prespojni panel 24xRJ45 cat.6, neoklopljen, 19", 1U, RAL7035 svijetlo siva			HSERU246GV
U/UTP cat.6, 4x2xAWG24/1, 300MHz, LS0H B2ca-s1a,d1,a1 plavi, bubanj 500m	68	19	HSKU423BP5
U/UTP inst. kabel cat.6, 4x2xAWG24/1, PVC, Eca, plavi Kutija 305m	69	18	HSEKU423P4