

Tehnički list za artikl: H6UTG30K0G

Prespojni kabel RJ45 UTP cat.6a 10GB, LSOH, sivi, 30.0m



Tehnički podaci

Kategorija	Cat.6
Sastav kabela	4x2xAWG26/7
Kabelski oklop	U/UTP
Materijal vodiča	Licnasta žica AWG 26/7 (0,457mm)
Konekcija	1:1
Brzina prijenosa	10Gbit
Broj parica	4
Oklop	Neoklopljen
Vanjski omotač kabela	LSOH
LED funkcija	bez LED
Mogućnost identifikacije	Spajalice u boji
Neto masa (kg)	0,99
Boja	siva
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	60

Tehnički podaci - nastavak

Temperaturno područje - Pogon (°C)	-20 do +60
Temperaturno područje - Instalacija (°C)	+0 do +50
Otpor (Ohm)	100 ± 5
Izolacijski otpor (MΩ*km)	> 2000MΩ/km
Kašnjenje uklopa (ns/m)	≤ 427ns/100m
Dielektrična čvrstoća - kontakt-kontakt (V)	500V DC
RoHS	Konformno
Impedancija petlje (Ω/km)	250
PoE	IEEE 802.3af
PoE+	IEEE 802.3at
UPoE	Ja
Duljina prespojnog kabela (m)	30,0

Tabela artikla

OPIS	KAT. BROJ
Prespojni kabel RJ45 UTP cat.6a 10GB, LS0H, sivi, 30.0m	H6UTG30K0G
Dodatni pribor	
fixLink modul RJ45 neoklopljen cat.6a AWG 24-22 PoE+, pak: 1 CKFVK000EP	HEKFMAUGI1
fixLink modul RJ45 neoklopljen cat.6a AWG 24-22 PoE+,pak: 24 CKFVK000	HEKFMAUGI2