

Tehnički list za artikl: HDCR100158

# IS-1 kolok. ormar 2d bez bočnih str

## 600x2000x1000 RAL9005



### SCHRACK-Info

**Compartments:** 2

**U/Compartment:** 21

**Material:**

Basic frame: 1.50mm steel sheet

Doors: 1.50mm steel sheet

Side panels: 1.50mm steel sheet

482.6 mm (19") mounting angles: 2.00mm steel sheet

**Finish:**

Frame and cladding parts: powder-coated

Internal fittings: galvanised

**Static load capability:** 25kg per U

**Frame clearance, front:** 112mm

**Installation depth:** 747mm

**Equipment:**

- 1 basic frame, demountable, with integrated 25-mm mounting hole pitch pattern on all sides
- 4 galvanised 482.6mm (19") mounting angles per compartment for cage nuts acc. to IEC 297 d EIA, including height unit labelling
- Lateral airflow routing panel at front of each compartment
- Per compartment, 1 single wing front door, passive venting (free clearance 81%), with swing handle, prepared for DIN profile half cylinder (30/10), 2- point locking system
- Per compartment, 1 single wing rear door, passive venting (free clearance 81%), with swing handle, prepared for DIN profile half cylinder (30/10), 2- point locking system

- 2 double-wing side panels, screw fastened n 1 top cover, single part, solid (only width 600) or with cable entry aperture (on width 800)
- Depending on the version, 2 or 3 solid partition plates
- 1 bottom cover, solid with cable entry apertures, depending on the model
- 1 or 2 cable ducts for B600 / 2 or 4 cable ducts for B800
- 4 levelling feet, incl. protective caps (provided)
- 1 earthing set, mounted (all flat components earthed, central earthing point)

#### Inspections/Norms

- Earthing in acc. with DIN VDE 0100-540
- Components in acc. with IEC 297-1/2 (19")


## Tehnički podaci

|                                |                     |
|--------------------------------|---------------------|
| Neto širina (mm)               | 600,00              |
| Neto visina (mm)               | 2.000,00            |
| Neto dubina (mm)               | 1.000,00            |
| Boja                           | RAL 9005 (jet crna) |
| Visinska jedinica              | 42                  |
| Neto masa (kg)                 | 165,00              |
| Min. temperatura okoline (°C)  | -10                 |
| Maks. temperatura okoline (°C) | 60                  |
| IP stupanj zaštite             | IP20                |

## Mjerne skice: IS-1 kolok. ormar 2d bez bočnih str 600x2000x1000 RAL9005



**Mjerne skice: IS-1 kolok. ormar 2d bez bočnih str 600x2000x1000 RAL9005**



OPIS

KAT. BROJ

IS-1 kolok. ormar 2d bez bočnih str 600x2000x1000 RAL9005

HDCR100158