


Tehnički list za artikl: HLP29TC01F

Optički prespojni kabel DX ST/UPC-SC/ UPC, 9/ 125µm OS2, LSOH

Žuti, 1.0m



SCHRACK-Info

Single mode patch cords are used for telecom networks and also used for high speed metropolitan and access network. The single-mode patch cables are equipped with an LSOH jacket. These comply with IEC or EIA-TIA standards. These singlemode enhanced patch cords are terminated with optimized connectors which give optimum optical performance.

FEATURES

- ST/UPC - SC/UPC connectors
- Low smoke zero halogen (LSOH) jacket
- 900 µm tight buffer
- Singlemode cabled fiber conforms to ITU-T G.657.A2, IEC 60793-2-50
- Duplex
- REACH, RoHS and SvHC materials compliant

APPLICATIONS

- CATV / Video
- Passive Optical Network PON
- WDM / DWDM
- FTTH
- Data centers
- Supports high speed multi channel video, data and voice services in metropolitan and access networks


- ATM, SONET and WDM



Tehnički podaci

Norma	IEC 61300-3-4 / IEC 61300-3-6
Utikač - Norma	IEC 61754
Kombinacija utičnica	SC/ST
Duljina prespojnog kabela (m)	1
Vlakno	singlemodno 9/125µm OS1
Vanjski omotač kabela	LS0H
Boja	žuta
Uklopno prigušenje tipično (dB)	≤0,25
Prigušenje povratnog toka tipično (dB)	≥50
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	60
Neto širina (mm)	180,00
Neto visina (mm)	250,00
Neto masa (kg)	0,08

Mjerne skice: Optički prespojni kabel DX ST/UPC-SC/UPC, 9/ 125µm OS2, LS0H



OPIS

KAT. BROJ

Optički prespojni kabel DX ST/UPC-SC/UPC, 9/125µm OS2,LSOH
žuti, 1.0m

HLP29TC01F