

Tehnički list za artikl: HSATLSA---

SAT LNB Quattro za razdjelnik, zaštita od vode, Ø40mm



SCHRACK info

The LNB is intended for use in SAT systems with multiswitches. The signals of the individual reception levels are output separately at the corresponding F-connectors.

- Only for multiswitch systems
- For the reception of DVB-S and DVB-S2 signals
- HDTV-compatible
- Extendable weather protection cap to protect the F-connections
- Nickel-plated F-connectors
- feed diameter 40 mm



Tehnički podaci

Neto duljina (mm)	125,00
Neto širina (mm)	85,00
Neto visina (mm)	75,00
Neto masa (kg)	0,26
Min. temperatura okoline (°C)	-30

Tehnički podaci - nastavak

Maks. temperatura okoline (°C)	60
Promjer dovoda (mm)	40
Primanje od	DVB-S and DVB-S2 signals (HDTV compatible)
Priključak	F . Kontakti niklovani
Broj izlaza	4
Produljiva kapa za zaštitu od vremenskih uvjeta	DA
Ulazna frekvencija	Low Band - 10.7 - 11.7 GHz High Band - 11.7 - 12.75 GHz
Izlazna frekvencija	Niski pojas - 950 ~ 1950 MHz Visoki pojas - 1100 ~ 2150 MHz
Frekvencija osciliranja	Low Band - 9,75 GHz $\pm$ 1,5 MHz High Band - 10.60 GHz $\pm$ 1.5 MHz
Noise Figure	Low Band - $\leq$ 1.0dB High Band - $\leq$ 1.0dB
Unakrsna polarizacijska izolacija	20 dB (Min.)
Ojačanje	55 ~ 70dB
Linearnost dobitka	$\pm$ 0.5 dB / 27 MHz
Tip reflektora	Offset
Fazni šum	100 dBc / Hz (@ 100kHz) 50 dBc / Hz (@ 1kHz) 75 dBc / Hz (@ 10kHz)
Image Rejection	45 dB (min).
Izlazni omjer (na temelju 75 Ω)	2.5 : 1 (max.)
Vrsta izlaznog priključka	75 Ω F-Connector
Polarization Control Voltage Range	11.5 ~ 14.0 V (Vertical Polarisation) 16.0 ~ 19.0 V (Horizontal Polarization) Continuous 22 kHz $\pm$ 4 kHz (High Band Selection)
Proizvod	LNB-ovi

OPIS	KAT. BROJ
SAT LNB Quattro za razdjelnik, zaštita od vode, Ø40mm	HSATLSA