

Tehnički list za artikl: HSEAIBH043

Univer.opt.kabel A/I-DQ(ZN)BH 4x50/125µm OM3, LS0H-3, Dca

nemetalna zaštita od glodavaca, crni, 8mm, 5000N



SCHRACK-Info

- For indoor- and outdoor- use in structured (data) wiring systems such as industrial backbone, campus backbone, building backbone (riser) and/or horizontal cabling. Support of all computer network applications, e.g. FDDI, Gigabit Ethernet and ATM.
- Suitable for direct burial.
- Easy to install in ducts, tunnels and trenches.

FEATURES AND BENEFITS

- These cables are all dielectric and therefore immune to lightning and electromagnetic interference (EMC-safe), spark-free and requires no earthing.
- Rodent protection.
- Predicted lifetime > 30 years.



Tehnički podaci

Broj vlakana	4
Neto promjer (mm)	7,90
Promjer- centralna cijev (mm)	4
Primarna zaštita (µm)	250 ± 15
Neto masa (kg)	0,07
Pogodan	Univerzalni kabel
Vodotijesnost	Ja
Zaštita od glodavaca	Ja
Očekivani vijek trajanja	> 30 godina
Kriptoanalizator (N/m)	≤ 10000
Vanjski omotač kabela	LS0H-3
Zaustavljanje plamena	Potvrđeno
Bezhalogena	Da
Gustoća dima	Potvrđeno
Euro-norma prema EN50575	Dca
Razvoj/gustoća dima	s2
Stvaranje gorećih kapljica	d1
Razvoj kiselosti/korozivnost	a1
Temperaturno područje - Transport/Skladištenje (°C)	-30 do +70
Temperaturno područje - Instalacija (°C)	-5 do +50
Temperaturno područje - Pogon (°C)	-30 do +70
Vlačna čvrstoća - dugoročna (N)	≤ 2500
Vlačna čvrstoća - kratkoročna (N)	≤ 5000
Radijus savijanja kabela - statički (Ø)	10 x Ø
Radijus savijanja kabela - dinamički (Ø)	15 x Ø
Radijus savijanja za vlakna i žile (mm)	> 25
Promjer oblika polja / okvira (µm)	50 ± 2,5 125 ± 1
Valna duljina (nm)	850 1300
Prigušenje (dB/km)	2,5 / 3,0 0,5 / 1,0
Raspon (MHz*km)	≥ 1500 ≥ 500
Ethernet 1 GB (m)	900 550
Ethernet -snaga 10GB (m)	300 300
Numerička apertura	0,20 ± 0,015
Indeks loma	1,482 1,477
Vlakno	multimodno 50/125µm OM3
Promjer (mm)	4
Min. temperatura okoline (°C)	-30
Maks. temperatura okoline (°C)	70

GUIDE TO INSTALLATION AND HANDLING

When laying and installing optical fibre cables it is vitally important not to exceed the specified values set for pulling tension, bending radii and temperature. The installation methods have to be in accordance with the common standards.

To ease insertion into tubes by means of compressed air or pulling wire, certified lubricants (e.g. paraffin) maybe used.

The use of soap or similar substances as lubricants is strictly prohibited.

If a cable needs to be fastened, constrictions ≥ 0.3 mm must be prevented.

The jelly filling inside the tubes can be removed using a tissue soaked in turpentine.

It is advisable to cap the cable-ends during storage.

Tabela artikla

OPIS	KAT. BROJ
Univer.opt.kabel A/I-DQ(ZN)BH 4x50/125µm OM3, LS0H-3, Dca nemetalna zaštita od glodavaca, crni, 8mm, 5000N	HSEAIBH043
Dodatni pribor	
Opt. razdjelnik, 4 niti, LC, 50/125µm OM3, izvlačivi, 19", 1U optički završeci umetnuti i pripremljeni za varenje, 19", 1U, RAL7035, klase B prema IEC 61753-1, PREMIUM	HSELS043LG
Opt. razdjelnik, 4 niti, SC, 50/125µm OM3, izvlačivi, 19", 1U optički završeci umetnuti i pripremljeni za varenje, 19", 1U, RAL7035, klase B prema IEC 61753-1, PREMIUM	HSELS043CG
Opt. razdjelnik, 4 niti, ST, 50/125µm OM3, izvlačivi, 19", 1U optički završeci umetnuti i pripremljeni za varenje, 19", 1U, RAL7035, klase B prema IEC 61753-1, PREMIUM	HSELS043TG
Čičak vezica crna 16mm x 4m	Q7KB0416-S
Čičak vezica plava 16mm x 4m	Q7KB0416-B
Čičak vezica crvena 16mm x 4m	Q7KB0416-R
Čičak vezica žuta 16mm x 4m	Q7KB0416-Y
Čičak vezica zelena 16mm x 4m	Q7KB0416-U