




Tehnički list za artikl: HSELS2400W

# FTTx n/ž kutija za vanj., 24 vlakana, prazna, Š200xV235xD67mm

RAL7035 svjetlo siva, uklj. tri modularna panela za spojnice s izrezima za: 12x LC-Dx, SC-Sx, ili E-2000®-Sx s vijcima, 9x SC-Dx ili 6xLC-QD s vijcima, 12x SC-Dx ili LC-QD s vijcima, 1 x komplet (30 kom.) cjevčica za zaštitu spoja s nosačem, IP54



## SCHRACK-Info

### Application

- Easy to mount splicebox for the indoor or outdoor construction of fibre optic distribution with the possibility of mounting a profile half cylinder
- Suitable for up to 24 optical fibres

### Technical Data

- Structured ASA (Acrylester-Styrol-Acrylnitril), extremely durable plastic, impact-resistant and weatherproof
- Cover locking by locking hooks with the option of sealing
- Splice cassette for easy installation and maintenance with maximum protection of the fibres with cross-out option and overlength tray
- Prepared for installation of profile half cylinder
- Strain relief for cables and patch cords
- Mounting option and fixation for gas - / water blockers available
- Patch cable outlet with flexible lamellar seal
- Modular adapter plate with cut-outs for fibre optic adapters included
  - Adapter plate 1: for up to 12x LC-Dx, SC-Sx or E-2000® -Sx
  - Adapter plate 2: for up to 9x SC-Dx or 6x LC-Quad
  - Adapter plate 3: for up to 12x SC-Dx, 6x LC-Quad without flange
- Equipped with 1x set (30 pcs) heat shrink splice protector for crimp splice holder
- Mounting option for 2x PCL splitter (40x4mm)
- Cable entry with 2x M20, 2x M25 cable gland possible
- Color: RAL7035 Light grey
- Protection class as per IEC 60529: IP54

### Climate area

- During transport: -25 °C bis +70 °C
- During installation: -5 °C bis +50 °C
- During operation: -5 °C bis +70 °C

### Mechanical Data

- Material: ASA, halogenfrei und schlagfest
- Dimensions:
  - Width: 200mm
  - Height: 235mm
  - Depth: 67mm
- Weight: 1,04kg

### Accessories

- HSELSZSH12: FO shrink splice protector 45mm for FTTx Spliceboxes HSELS1200W / HSELS2400W
- DV900333--: Half cylinder lock keyed EK 333 including 1 key. (Countersunk screw M5x12mm is required)
- HSELSZMK01: Pole attachment for splicebox HSELSxx00W, diameter 60-215mm
- HSELSZMK02: Pole attachment for splicebox HSELSxx00W, diameter 60-325mm

## Tehnički podaci

|                  |        |
|------------------|--------|
| Neto širina (mm) | 200,00 |
|------------------|--------|

## Tehnički podaci - nastavak

|                                |        |
|--------------------------------|--------|
| Neto visina (mm)               | 235,00 |
| Neto dubina (mm)               | 67,00  |
| Neto masa (kg)                 | 1,04   |
| Min. temperatura okoline (°C)  | -5     |
| Maks. temperatura okoline (°C) | 70     |

## Tabela artikla

| OPIS                                                                                                                                                                                                                                                                                                                     | KAT. BROJ  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| FTTx n/ž kutija za vanj., 24 vlakana, prazna, Š200xV235xD67mm<br>RAL7035 svjetlo siva, uklj. tri modularna panela za spojnice s izrezima za: 12x LC-Dx, SC-Sx, ili E-2000®-Sx s vijcima, 9x SC-Dx ili 6x LC-QD s vijcima, 12x SC-Dx ili LC-QD s vijcima, 1 x komplet (30 kom.) cjevčica za zaštitu spoja s nosačem, IP54 | HSELS2400W |
| <b>Dodatni pribor</b>                                                                                                                                                                                                                                                                                                    |            |
| Učvršćenje za stup n/ž kutije HSELSxx00W, promjera 60-215mm<br>nehrđajući čelik, za rasvjetne stupove i sl., uklj. materijal za učvršćenje                                                                                                                                                                               | HSELSZMK01 |
| Učvršćenje za stup n/ž kutije HSELSxx00W, promjera 60-325mm<br>nehrđajući čelik, za rasvjetne stupove i sl., uključivo materijal za učvršćenje                                                                                                                                                                           | HSELSZMK02 |
| Optička cjevčica za zašt. spojeva, 45mm, prozirna<br>1 pak = 100 komada                                                                                                                                                                                                                                                  | HSELSZSH12 |
| Umetak polucilindar brave EK 333 s 1 ključem i vijak M5<br>uključujući 1x upušteni vijak M5x16mm V2A                                                                                                                                                                                                                     | DV900333S  |