

Tehnički list za artikl: HSELS249DP

Optički razdjelnik, 24xSC/APC, 9/ 125μm OS2, izvlačivi, 19", 1U

prema IEC 61753-1, RAL7035, izvlačiva ladica



Schrack-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 SC/APC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland

- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
 - Chassis: 1,0mm
 - Sliding tray: 1,25mm
 - Frontpanel: 1,4mm
 - 19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
 - up to 12 fibres: 1 splice-cassette
 - up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Tehnički podaci

Neto širina (mm)	480,00
Neto visina (mm)	44,00
Neto dubina (mm)	242,00
Neto masa (kg)	2,53
Vlakno	9/125 OS2 Singlemode / G.652.D
Boja	RAL 7035 (svijetlo siva)
Uklopno prigušenje tipično (dB)	< 0,2
Prigušenje povratnog toka tipično (dB)	> 50
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	24

Tabela artikla

OPIS	KAT. BROJ
Optički razdjelnik, 24xSC/APC, 9/125µm OS2, izvlačivi, 19", 1U prema IEC 61753-1, RAL7035, izvlačiva ladica	HSELS249DP
Dodatni pribor	
Optička cjevčica za zaštitu spoja 60mm	HELSP00011
Optička cjevčica za zaštitu spoja 40mm	HELSP00010

Tabela artikla

OPIS	KAT. BROJ
Dodatni pribor	
Alat za čišćenje optičkih utikača SC, ST, FC i E2000 Pogodno za UPC i APC utikače. Više od 1000 ciklusa čišćenja.	HSELSZT002
Mjerač snage s integriranim laserom (VFL) za optičke spojeve PAŽNJA: ovo je izvor svjetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi. Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svjetla.	HSELSZT003
Optički pr. kabel DX SC-APC/SC-APC, 9/125µm OS2, LSOH, 1 m žuti, 1.0m, LSH0	HLP29DD01F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LSOH-3, 1 m žuti, 1.0m, LSH0	HLP29MD01F
Optički pr. kabel DX SC-APC/SC-APC, 9/125µm OS2, LSOH-3, 2m žuti, 2.0m, LSH0	HLP29DD02F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LSOH-3, 2m žuti, 2.0m, LSH0	HLP29MD02F
Optički pr. kabel DX SC-APC/SC-APC, 9/125µm OS2, LSOH-3, 3m žuti, 3.0m, LSH0	HLP29DD03F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LSOH-3, 3m žuti, 3.0m, LSH0	HLP29MD03F
Optički pr. kabel DX SC-APC/SC-APC, 9/125µm OS2, LSOH-3, 5m žuti, 5.0m, LSH0	HLP29DD05F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LSOH-3, 5m žuti, 5.0m, LSH0	HLP29MD05F
Optički pr. kabel DX SC-APC/SC-APC, 9/125µm OS2, LSOH-3, 10m žuti, 10.0m, LSH0	HLP29DD10F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LSOH-3, 10m žuti, 10.0m, LSH0	HLP29MD10F