

Tehnički list za artikl: HVSMRJ5UBS

Utični modul RJ45 cat.5e, neoklopljen (SFA), crni



SCHRACK-Info

TRANSMISSION PERFORMANCE

- Meet all requirements specified in connecting hardware requirement of ANSI/TIA-568-C.2, Category 5e

ELECTRICAL

- Electrical Insulation Resistance: 500MΩ min. 100VDC
- Dielectric Withstanding Voltage : 1000VDC or a.c. Peak Contact to Contact 60Hz for 1 minute

MECHANICAL

- Insertion / Extraction Life: 750 Cycles Minimum
- IDC Wire Gauge: 22 ~ 24 AWG

PHYSICAL

- Housing: High-Impact, Flame-Retardant Plastic, UL 94V-0
- Spring Wire: Phosphor Bronze Alloy Plated with 50μ-inch of Gold
- IDC: Phosphor Bronze Alloy with 100μ-inch 100% Sn Alloy

Tehnički podaci

Neto duljina (mm)	35,00
Neto širina (mm)	17,00

Tehnički podaci - nastavak

Neto visina (mm)	26,00
Neto masa (kg)	0,01
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	60

Tabela artikla

OPIS	NVP (%)	MASA BAKRA (kg/km)	KAT. BROJ
Utični modul RJ45 cat.5e, neoklopljen (SFA), crni			HVSMRJ5UBS
Dodatni pribor			
Alat za spajanje na HVSMRJ5UWS / HVSMRJ6UWS			HVSTOOL01S
U/UTP inst. kabel cat.5e, 4x2xAWG24/1, PVC,Eca,plavi,305m	69	15	HSEKU424P1
U/UTP inst. kabel cat.5e, 4x2xAWG24/1,PVC,Eca,sivi,305m	69	15	HSEKU424P0
U/UTP inst. kabel cat.5e, 4x2xAWG24/1,LSOH,Eca,plavi,305m	69	15	HSEKU424H1
Prespojni panel 19", prazan, za 24 modula (SFA)(SFB), 1U svjetlo siva, jezičac prespojnog kabla okrenut prema dolje			HSER0240GS
Adapter za DIN profil, prazan, za 1 modul (SFA)(SFB)			HSERH010GS
Svjetlo siva			