

Tehnički list za artikl: ILT30800-A

NV odlazno polje 800A, 822mm, 50x10 sabirnički sustav



SCHRACK-Info

- **General** : Type-tested Modul 2000TT outgoing fields for HRC in-line fuse switches up to 630A
- **Material** :
 - Corpus: 1.5mm galvanised sheet steel
 - Doors: Single door and double door: 1.5mm sheet steel
- **Door** :
 - Made of sheet steel and equipped with M8 threaded bolts for earthing. Enclosures in widths 602mm and 822mm are single door versions, enclosures in widths 1042mm and 1242mm are double door versions
 - On single door enclosures, the door is mounted on three double-sided hinges for right-hand opening (=hinged right). On double door enclosures, hinges are not reversible, the left door wing is locked separately with an inner three-point lock
- **Lock** : Three-point rod lock with swing handle (without lock insert), does not slide inward. The standard lock can be exchanged for profile half cylinders (DIN cylinders) from the range of accessories. Double doors are designed with a left-side inner pivot lever
- **Roof** :
 - Two cut-outs for cable entries at widths 602mm and 822mm, three cut-outs at width 1042mm and four cut-outs at width 1242mm
 - Gland plates from our accessories are required for completion
- **Side cut-out** : Contacting possibility for the main busbar. 1 PU (=2 pieces) side covers **IL920001** per enclosure is necessary
- **Baying kit** : A baying kit for baying a second Modul 2000TT enclosure is included
- **Plinth** : 100mm high with cable entry options on the sides. Optionally it is possible to stack two 100mm high plinths on top of each other

- **Protection class** : I
- **Degree of protection** : Standard IP31 up to 1250A, without door it's possible up to 1600A, with corresponding components from our accessories (exhaust filter, gland plates and plinths) IP54 is possible up to 1250A
- **Impact resistance** : IK10
- **Finish** : Textured powder coating
- **Color** : RAL 7035 (Light grey)
- **Delivery includes** :
 - Enclosure with plinth
 - Door with earthing studs
 - Main busbar system
 - Transparent polycarbonate covers
 - Transport connection for main busbar system
 - Baying kit for one more enclosure

Delivered on an Euro-pallet



Tehnički podaci

Neto širina (mm)	822,00
Neto visina (mm)	2.140,00
Neto dubina (mm)	400,00
Neto masa (kg)	190,00
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
IP stupanj zaštite	IP31
Materijal	Čelični lim
Boja	RAL 7035
Širina (mm)	822
Visina (mm)	2138
Dubina (mm)	400
Disipacija snage (W)	-859,00
ŠxVxD mm	822x2140x400
EAN	9004840837247

OPIS	MASA BAKRA (kg/km)	KAT. BROJ
NV odlazno polje 800A, 822mm, 50x10 sabirnički sustav		ILT30800-A

Potrebni pribor

Tabela artikla

OPIS	MASA BAKRA (kg/km)	KAT. BROJ
Potrebni pribor		
Bočni pokrovi ormara Modul2000TT (pak.=2 kom.)		IL920001
Prirubnica, izolacijska, slijepa, IP66		IL958001-A
Prirubnica, izolacijska, IP55, 9xØ3-20, 1xØ3-40, 2xØ3-70mm pjenasta guma		IL958007-A
Prirubnica, izolacijska, 4xM16, 6xM25/16, 8xM32/20		IL958002-A
Prirubnica, izolacijska, 2xM20, 8xM25/16, 4xM32/20, 1xM50/32 IP66		IL958003-A
Prirubnica, izolacijska, 2xM16, 12xM20, 2xM40/25, 2xM50/32 IP66		IL958004-A
Prirubnica, izolacijska, IP66, 24xM16, 13xM20		IL958005-A
Prirubnica, izolacijska, IP55, 44xØ3-14, 3xØ3-21, 2xØ3-30mm pjenasta guma		IL958006-A
Dodatni pribor		
Modularni okvir 3-42K komplet, metalne maske, NH za NV pruge		ILTAK342
NV rastavna pruga vel.00 160A, 3P, M8, sustav 100mm NH-Leiste, für 100mm-Sammelschienensystem, M8, 3-polig	420	ISA05261
Dvostruki adapter za ARROW LINE vel.00 - 100mm na 185mm Series ARROW-LINE	469	ISA05326
Pokrov za poravnanje pruga po visini, za vel.00 (2 kom.) za niveliranje pokrova sa veličinama 1-3		ISA05329
NV rastavna pruga vel.1 250A, 3P, M10, sustav 185mm Arrow Line	1943	ISA05305
NV rastavna pruga vel.2 400A, 3P, M12, sustav 185mm Arrow Line	1952	ISA05311
NV rastavna pruga vel.3 630A, 3P, M12, sustav 185mm Arrow Line	2662	ISA05320
NV rastavna pruga vel.1 250A, 3P, V-stezaljka, sustav 185mm Arrow Line	1965	ISA05306
NV rastavna pruga vel.2 400A, 3P, V-stezaljka, sustav 185mm Arrow Line	1965	ISA05312
NV rastavna pruga vel.3 630A, 3P, V-stezaljka, sustav 185mm Arrow Line	2685	ISA05321
NV rastavna pruga ARROW II, veličina 00, 3polna, 100mm, M8 montaža isključivo sa strujnim mjernim transformatorom	391	ISA05340
NV rastavna pruga ARROW II veličina 1, 3polna, 185mm, M12 Version to integrate current transformers	1948	ISA05341

Tabela artikla

OPIS	MASA BAKRA (kg/km)	KAT. BROJ
Dodatni pribor		
ARROW-LINE, vel.2, 3P, V-stezaljke, za strujni trafo Version to integrate current transformers	1948	ISA05342
ARROW-LINE, vel.3, 3P, V-stezaljke, za strujni trafo Version to integrate current transformers	2633	ISA05343
Pokrov gornjih/donjih stezaljki rastavne pruge, za vel.1 - 3 Za pruge serije ARROW II		ISA05334
Pokrov praznog otvora, 50mm, kad pruga 185mm nije ugrađena For the cover for prefabricated cutouts for HRC inline fuses ARROW-LINE in the 185mm busbar system		ISA05356
Pokrov praznog otvora, 100mm, kad pruga 185mm nije ugrađena For the cover for prefabricated cutouts for HRC inline fuses ARROW-LINE in the 185mm busbar system		ISA05357
Umetak polucilindar "double-bit" brave 5mm, metalni, 1109-U		IU001906
Izlazni filter, 252x252x38mm, IP54 IUKNF4523A		IUKNE450
Podnožje, prednji dio, za razdjelnike širine 3A, IP31		IL957300
Bočni dio postolja 400mm (1 par) IP31 inklusive Schrauben, Ausschnitt 290x50mm		IL090140
Prednja ploča 3B18 metalna with cutout for NH fuse switch		ILT56318-A
Spremnik za dokumentaciju, samoljepljivi, A4		ASDRA400
Transportne ušice M12 za AC i KC ormare PAK=4 komada		ACLE9301
Slijepa traka, mogućnost plombiranja ne može se s prednje strane		IL900112-F