

Tehnički list za artikl: INSP141D--

Servisna sklopka, 4-pola, 315A, IP65, zaključavanje

Izvedba/tip Servisna sklopka, Nazivna struja 315A, Polovi 4, IP stupanj zaštite IP65 (housing), IP10 (terminals), mogućnost zaključavanja



Tehnički podaci

Izvedba/tip	Servisna sklopka
Nazivna struja (A)	315
Polovi	4
Način montaže	Nadgradna
Norma	IEC 60947, EN 60947, VDE 0660
Nazivni napon izolacije [Ui] (V)	690
Nazivni udarni podnosivi napon [Uimp] (V)	6000
Nazivna kratkotrajno podnosiva struja Icw	1000
Nazivna struja kratkog spoja	10kA @ 440V / 6kA @ 690V
Frekvencija (Hz)	50/60
Operating Current	AC-3 - 690V - 47A AC-23A - 690V - 57A AC-3 - 400V - 195A AC-21A - 690V - 315A AC-23A - 400V - 230A




Tehnički podaci - nastavak

Switching Capacity	AC-23A - 400V - 132kW AC-3 - 690V - 45kW AC-23A - 690V - 55kW AC-3 - 400V - 110kW
According to UL 508 / CSA	
Radni napon AC (V)	600
Thermal rated continuous current (A)	315
Priključak	
Konvencionalna termička struja Ith (A)	315
MOment pritezanja (Nm)	3
Presjek priključnih vodiča, višezilni kabel (mm²)	16-185
Presjek priključnih vodiča, Jednožični (mm²)	16-185
Presjek priključnih vodiča, finožični kabel s tuljkom (mm²)	16-150
Retrofit contacts	
Pomoćni kontakti	Maximum 2x INSHK001-- permitted. 1x INSHK001-- can be snapped on to the left side of the main contact and 1x INSHK001-- to the right side of the main contact. Maximum configuration 2x NC contact / 2x NO contact. The switching behavior is the same regardless of whether the auxiliary contact is snapped on to the left or right side of the main contact.
Neutral conductor contacts	Neutral conductor early-make, late-break design (closes before and opens after the phase conductors to prevent voltage displacement)
Radna temperatura	-25°C to +55°C
Mehanički životni vijek	100000 switching cycles
Gubitak snage po polu (W)	39
Zaštita od dodira	finger-proof and back-of-hand-proof according to VDE 0106 Part 100
IP stupanj zaštite	IP65 (housing), IP10 (terminals)
Lockable	With 3 locks, each with a shackle lock diameter of 4-6 mm
Neto duljina (mm)	225,00
Neto širina (mm)	374,00
Neto visina (mm)	374,00
Min. temperatura okoline (°C)	-25
Maks. temperatura okoline (°C)	55

Schaltbild INSP141D--



Maßbild INSP141D--



[mm]

Montageanleitung INSHK Hilfskontakte

Hilfskontakt
Auxiliary contact
INSHK001--



Tabela artikla

OPIS	KAT. BROJ
Servisna sklopka, 4-pola, 315A, IP65, zaključavanje	
Izvedba/tip Servisna sklopka, Nazivna struja 315A, Polovi 4, IP stupanj zaštite IP65 (housing), IP10 (terminals), mogućnost zaključavanja	INSP141D
Dodatni pribor	
Pomoćni kontakt 1NO/1NC za INSR, INSP i INSA	
Nije dopušteno koristiti za INSE, Izvedba/tip Pribor, IP stupanj zaštite IP20 (terminals)	INSHK001