

Tehnički list za artikl: INSR3463--

Preklopna sklopka 1-0-2, montaža na DIN nosač, 4-pola, 63A

Izvedba/tip 1-0-2, Nazivna struja 63A, Polovi 4, IP stupanj zaštite IP40 (front), IP00 (terminals)



Tehnički podaci

Izvedba/tip	1-0-2
Nazivna struja (A)	63
Polovi	4
Način montaže	DIN nosač
Norma	IEC 60947, EN 60947, VDE 0660
Nazivni napon izolacije [Ui] (V)	690
Nazivni udarni podnosivi napon [Uimp] (V)	6000
Nazivna kratkotrajno podnosiva struja Icw	1000
Nazivna struja kratkog spoja	10kA @ 440V / 6kA @ 690V
Kratkospojna zaštita, maks. rastalni osigurač	63
Frekvencija (Hz)	50/60


Tehnički podaci - nastavak

Operating Current	AC-22A - 690V - 63A AC-3 - 690V - 17A AC-3 - 230V - 38A AC-23A - 400V - 41A AC-23A - 690V - 21A AC-21A - 690V - 63A AC-3 - 400V - 36A AC-23A - 230V - 38A
Switching Capacity	AC-3 - 690V - 15kW AC-23A - 230V - 11kW AC-23A - 400V - 22kW AC-23A - 690V - 18.5kW AC-3 - 230V - 11kW AC-3 - 400V - 18.5kW
According to UL 508 / CSA	
Tip priključka	UL/CSA - AWG 14-6
Radni napon AC (V)	600
Thermal rated continuous current (A)	63
Active Power	3x240VAC - 15Hp 3x120VAC - 5Hp 3x480VAC - 25Hp 1x240VAC - 10Hp 3x600VAC - 30Hp 1x120VAC - 3Hp
Priključak	
Konvencionalna termička struja Ith (A)	63
MOment pritezanja (Nm)	3
Presjek priključnih vodiča, višezilni kabel (mm ²)	2,5-16
Presjek priključnih vodiča, Jednožični (mm ²)	2,5-16
Presjek priključnih vodiča, finožični kabel s tuljkom (mm ²)	2,5-16
Retrofit contacts	
Pomoćni kontakti	Maximum 2x INSHK001 -- permitted. 1x can be snapped onto the left side of the main contact and 1x onto the right side of the main contact. Maximum configuration 2x NC contacts / 2x NO contacts (1x NC contact / 1x NO contact per switching position). ATTENTION! Switching behavior is not the same! In switching position "1", only the auxiliary contacts that have been snapped onto the corresponding main contact will switch. In switching position "2", only the auxiliary contacts that have been snapped onto the corresponding main contact will switch.
Neutral conductor contacts	Neutral conductor early-make, late-break design (closes before and opens after the phase conductors to prevent voltage displacement)
Radna temperatura	-25°C to +55°C
Mehanički životni vijek	100000 switching cycles


Tehnički podaci - nastavak

Gubitak snage po polu (W)	3,60
Zaštita od dodira	finger-proof and back-of-hand-proof according to VDE 0106 Part 100
IP stupanj zaštite	IP40 (front), IP00 (terminals)
Lockable	No
Neto duljina (mm)	89,40
Neto širina (mm)	78,40
Neto visina (mm)	45,00
Min. temperatura okoline (°C)	-25
Maks. temperatura okoline (°C)	55

Schaltbild INSR3463--



Maßbild INSR3463--



Montageanleitung INSHK Hilfskontakte

Hilfskontakt
Auxiliary contact
INSHK001--



Montageanleitung INSR Hutschienenmontage Schalter



Tabela artikla

OPIS	KAT. BROJ
Preklopna sklopka 1-0-2, montaža na DIN nosač, 4-pola, 63A	INSR3463
Izvedba/tip 1-0-2, Nazivna struja 63A, Polovi 4, IP stupanj zaštite IP40 (front), IP00 (terminals)	
Dodatni pribor	
Pomoćni kontakt 1NO/1NC za INSR, INSP i INSA	INSHK001
Nije dopušteno koristiti za INSE, Izvedba/tip Pribor, IP stupanj zaštite IP20 (terminals)	