

Tehnički list za artikl: IP3211799-

Feed-through terminal block PTS 2, 5

Push-in connection, cross section: 0.14 mm² - 4 mm², AWG: 26 - 12, width: 5.2 mm, color: grey, NS 35/7.5, NS 35/15



Tehnički podaci

Neto dubina (mm)	43,00
Neto širina (mm)	5,20
Neto visina (mm)	49,00
Neto masa (kg)	0,01
EAN	4046356499484
Disipacija snage (W)	0,77
Min. temperatura okoline (°C)	-40
Maks. temperatura okoline (°C)	120
Osnovna oznaka	Stežaljka
Sistem	Push-In
Serijski	PT
Izvedba/tip	Prolazne stezaljke
Maks. presjek, kruti vodič (mm ²)	4
Maks. presjek, fleksibilni vodič (mm ²)	2,50
Maks. presjek, savitljiva žica s ferulom (mm ²)	2,50
Min. presjek, kruti vodič (mm ²)	0,14
Min. presjek, fleksibilni vodič (mm ²)	0,14

Tehnički podaci - nastavak

Min. poprečni presjek fleksibilni s kablskim završetkom (mm ²)	0,14
Presjek (mm ²)	2,5
Boja	siva
Nazivna struja (A)	24

Tabela artikla

OPIS	KAT. BROJ
Feed-through terminal block PTS 2,5	
Push-in connection, cross section: 0.14 mm ² - 4 mm ² , AWG: 26 - 12, width: 5.2 mm, color: grey, NS 35/7.5, NS 35/15	IP3211799
Dodatni pribor	
Koncový držák CLIPFIX 15, montáž na lištu NS 15	
sivi	IP3022263
Krajnji držač CLIPFIX 35-5 za NS 35/7,5 ili 35/15	
s mogućnošću označavanja, širina: 5, 15 mm, sivi	IP3022276
Krajnji držač CLIPFIX 35, za NS 35/7,5 ili 35/15	
s mogućnošću označavanja, širina: 9,5 mm, sivi	IP3022218
Krajnji držač E/UK	
End clamp, Width: 9.5 mm, Height: 35.3 mm, Length: 50.5 mm, Color: gray	IP1201442
Krajnji držač E/UK 1	
End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray	IP1201413
Krajnji držač E/MBK	
Krajnji držač, Širina: 6,2 mm, Boja: siva	IP1401637
Krajnji držač E/MK 1	
Krajnji držač, Širina: 6 mm, Boja: siva	IP1421659
Krajnji držač E/NS 35 N	
Širina: 9,5 mm, Boja: siva	IP0800886
Horizontalne oznake (1-10) za redne stezaljke širine 5.2mm	
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	IP10500171
Horizontalne oznake (11-20) za redne stezaljke širine 5.2mm	
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	IP10500172
Horizontalne oznake (21-30) za redne stezaljke širine 5.2mm	
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	IP10500173
Označna traka ZB 5, brojevi 31-40	
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	IP10500174

Tabela artikla

OPIS	KAT. BROJ
Dodatni pribor	
Označna traka ZB 5, brojevi 41-50	IP10500175
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	
Označna traka ZB 5, brojevi 51-60	IP10500176
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	
Označna traka ZB 5, brojevi 61-70	IP10500177
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	
Označna traka ZB 5, brojevi 71-80	IP10500178
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	
Označna traka ZB 5, brojevi 81-90	IP10500179
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	
Označna traka ZB 5, brojevi 91-100	IP1050017H
Traka sa lomljivim oznakama, bijela, za redne stezaljke širine: 5.15mm, natpisno polje: 5.15 x 10.5mm	
Ozn. traka ravna ZBF 5 , brojevi 1-10	IP08086711
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Ozn. traka ravna ZBF 5 , brojevi 11-20	IP08086712
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Ozn. traka ravna ZBF 5 , brojevi 21-30	IP08086713
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Ozn. traka ravna ZBF 5 , brojevi 31-40	IP08086714
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Ozn. traka ravna ZBF 5 , brojevi 41-50	IP08086715
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Ozn. traka ravna ZBF 5 , brojevi 51-60	IP08086716
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Ozn. traka ravna ZBF 5 , brojevi 61-70	IP08086717
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Ozn. traka ravna ZBF 5 , brojevi 71-80	IP08086718
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Ozn. traka ravna ZBF 5 , brojevi 81-90	IP08086719
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Ozn. traka ravna ZBF 5 , brojevi 91-100	IP0808671H
Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm	
Kratkospojnik (utični) za 2 stezaljke, FBS 2-5	IP3030161
Korak: 5.2mm, duljina: 22.7mm, širina: 9mm, boja: crvena	
Mostić za utiskivanje FBS 3-5	IP3030174
Plug-in bridge, pitch: 5.2 mm, length: 22.7 mm, width: 14.2 mm, poles: 3, color: red	
Mostić za utiskivanje FBS 4-5	IP3030187
Plug-in bridge, pitch: 5.2 mm, length: 22.7 mm, width: 19,4 mm, poles: 4, color: red	

Tabela artikla

OPIS	KAT. BROJ
Dodatni pribor	
Mostić za utiskivanje FBS 5-5 Plug-in bridge, pitch: 5.2 mm, length: 22.7 mm, width: 24.6 mm, poles: 5, color: red	IP3030190
Kratkospojnik (utični) za 10 stezaljki, FBS 10-5 Korak: 5.2mm, duljina: 22.7mm, širina: 50.6mm, boja: crvena	IP3030213
Mostić za utiskivanje FBS 20-5 Plug-in bridge, pitch: 5.2 mm, poles: 20, color: red	IP3030226
Mostić za utiskivanje FBSR 2-5 Plug-in bridge, pitch: 5.2 mm, poles: 2, color: red	IP3033702
Mostić za utiskivanje FBSR 3-5 Plug-in bridge, pitch: 5.2 mm, poles: 3, color: red	IP3001591
Mostić za utiskivanje FBSR 5-5 Plug-in bridge, pitch: 5.2 mm, poles: 5, color: red	IP3001593
Adapter za testiranje PAI-4-N GY Test adapter, color: grey	IP3032871
Odvijač 0,6 x 3,5 (SZF 1-0,6x3,5) Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip	IP1204517