

Tehnički list za artikl: IU070118--

19" napojna letva sa 6xšuko+prenap. zašt. i filter, 1U

filter frekvencije, ALU, 1U, kabel 2m, RAL7035



SCHRACK info

Sockets:

- DIN 49440, eximinated: VDE0620-1;
- 2-pole with earthing contact;
- 16A/3680W, AC250V, IP20;
- colour RAL7035, 35° turned;

Connection:

- non rewireable, Endcaps riveted, inside wiring without euro terminal
- 2,0m H05VV-F 3G1,5mm² black with german type plug

Profile:

- 1U, ALU, anodized
- Length: 438,5mm

Plastic material:

- RAL7035, PA6, fibre glass 30%, Glow wire test up to 850°C; V1

Overvoltage protection with filter:

- SPD Typ 3, Uc 250V~, IL 16A, Ip 6,5 kA
- L-PE; N-PE; L-N < 1,8kV
- Ta < 25ns
- Line and frequency filter for voltage peaks up to 30MHz

Mounting brackets:

- Steel sheet
- For fixing in 4 positions each 90°

Extent of delivery:

- 1x PDU
- 2x mounting brackets
- 1x instruction manual

Tehnički podaci

Neto širina (mm)	483,00
Neto visina (mm)	44,00
Neto dubina (mm)	44,00
Neto masa (kg)	0,87
Min. temperatura okoline (°C)	5
Maks. temperatura okoline (°C)	45
Boja	RAL 7035 (svijetlo siva)

Tabela artikla

OPIS	KAT. BROJ
19" napojna letva sa 6xšuko+prenap. zašt. i filter, 1U filter frekvencije, ALU, 1U, kabel 2m, RAL7035	IU070118
Dodatni pribor	
Okomiti nosač nap. letve za 800mm širine DS i DSZ ormara, 1U 1 pak = 2 kom., montaža na okomitu vodilicu, uklj. montažni set	DSPDU010
Okomiti nosač nap. letve za 600 i 800mm širine DSS ormara 1U, 1 pak = 2 kom., za napojne letve s 19" montažom, montaža na kućište ormara, uklj. montažni set	DSSPDU010
Okomiti nosač nap. letve za 600 i 800mm širine DSS ormara 2U, 1 pak = 2 kom., za napojne letve s 19" montažom. Montaža na kućište ormara, uklj. montažni set	DSSPDU021
Kabel za napajanje šuko - C13 ženski, crni, 1.8m	Q7130121
Kabel za napajanje šuko - C13 ženski, crni, 3m	Q7130059
Kabel za napajanje, shuko - C13 ženski 90°, crni, 5m	Q7170732
Kabel za napajanje Euro - Euro8, crni, 1.8m	Q7172506
Napojni kabel, shuko - C5 (trokut) ženski, crni, 1.8m	Q7172902