

Tehnički list za artikl: KCOX206060

Ormar za vanjsku upo. jednokrilni IP55 2000x600x600 (VxŠxD)

RAL7035, nehrđajući čelik, s izlaznim filterom, s poklopcem za zaštitu od mlaza vode i s montažnom pločom



SCHRACK-Info

- **Material :**
 - Frame: 1,5 mm stainless steel
 - Doors: 2 mm stainless steel
 - Rear panel: 1.5 mm stainless steel
 - Roof panel: 1.5 mm stainless steel
- **Mounting plate :** 3 mm galvanised sheet steel. Double folded, mounted in the enclosure, fully adjustable in depth in 25 mm increments with depth adjustment brackets ACMPD002. As insertion aid of the mounting plate we recommend the use of slide-in rails ACCLT600 (for depth 600 mm). The slide-in rails are inserted in the floor, after sliding and fixing of the mounting plate they can be removed and reused in the next enclosure
- **Bottom plates :** 1 mm galvanised sheet steel, divided in two parts
- **Frame :** Folded and seam welded reversed open profile with 25 mm hole pattern according to DIN 43660. Including inside circumferential hole pattern
- **Door :** On single door enclosures, the door is mounted on four double-sided hinges allowing left- or right-hand opening. On double door enclosures, hinges are not reversible. Doors for left-hand opening have to be ordered separately. All door panels include the door mounting frame with 25 mm hole pattern. The left Z-wing is locked separately with an inner three-point lock

- **Lock** : Four-point rod lock with push-pull handle with spring adjustment and 5 mm DIN double-bit key lock (DDB), does not slide inward. The standard lock can be exchanged for profile half cylinder (DIN cylinder) and other inserts from the range of accessories. Double doors are designed with a left-side inner pivot lever
- **Rear panel** : Mounted with M6 torx screws. Replacement against additional door from the back side is possible. For 1600 mm wide enclosures the rear panel is divided
- **Roof panel** : Removable
- **Earthing** : All panels are earthed through their fittings and are equipped with a separate earthing stud
- **Degree of protection** : Single door and double door IP55
- **Impact resistance** : IK10
- **Finish** : Textured powder coating with UV protection
- **Color** : RAL7035 (Light grey)
- **Delivery includes** : Enclosure with door, rear panel, closed roof panel, bottom plates and mounting plate. Delivered on a pallet.



Tehnički podaci

Neto širina (mm)	600,00
Neto visina (mm)	2.000,00
Neto dubina (mm)	600,00
Neto masa (kg)	167,00
Min. temperatura okoline (°C)	-40
Maks. temperatura okoline (°C)	80
IP stupanj zaštite	IP55
Klasa zaštite	I
Materijal	Nehrđajući čelik 1.4016 (AISI 430)
Boja	RAL 7035 (svijetlo siva)
Širina (mm)	600
Visina (mm)	2000
Dubina (mm)	600
Debljina zidova kućišta (mm)	1
Montažne ploče	Galvanizirani čelik 3mm
Debljina stijenke montažne ploče (mm)	3
Montažna poča - širina (mm)	497
Montažna ploča - visina (mm)	1891
Debljina stijenke vrata (mm)	2
Broj podnih limova	2
Opteretivost vrata (kg)	100
Broj vrata	1
Širina podnog lima (mm)	457
Roof panel thickness (mm)	1,50
Rear panel thickness (mm)	1,50
Corrosion class	C3-M
Tip	Samostojeći ormar

Tehnički podaci - nastavak

Opterećenost montažne ploče (kg)	700
Disipacija snage (W)	-684,00


Mjerne skice: Ormar za vanjsku upo. jednokrilni IP55 2000x600x600 (VxŠxD)

Tabela artikla

OPIS	KAT. BROJ
Ormar za vanjsku upo. jednokrilni IP55 2000x600x600 (VxŠxD) RAL7035, nehrđajući čelik, s izlaznim filterom, s poklopcem za zaštitu od mlaza vode i s montažnom pločom	KCOX206060
Dodatni pribor	
INOX podnožje prema širini ormara 600x100mm (ŠxV) Isporuka sadrži prednji i stražnji element podnožja (par, prema širini ormara), RAL7046 (Tele siva 2)	KCSOBX0601
INOX podnožje prema dubini ormara 600x100mm (ŠxV) Isporuka sadrži lijevi i desni element (par, prema dubini ormara) te 4 (predmontirana) kutna elementa, RAL7046 (Tele siva 2)	KCSOTX0601
Krović s ventilatorom (s filterom) 540m ³ /h, 600x600mm (ŠxV) Izrađen od aluminijske, RAL7035, montaža na INOX ormar KCIX206060 i outdoor ormar KCOX206060	KCRC6060F
Krović s izlaznim filterom, 600x600mm (ŠxV) Izrađen od aluminijske, RAL7035, montaža na INOX ormar KCIX206060 i outdoor ormar KCOX206060	KCRC6060E
Klizna šina za umetanje montažne ploče u ormar dubine 600mm za ormare serije AC/KC, isporuka u paru	ACCLT600
Transportne ušice M12 za AC i KC ormare PAK=4 komada	ACLE9301
Zakretna ručica bez umetka, crna, feder opruga without insert	ACLSC502
Adapter za polucilindar, za ASLSC501-S za izvlačivu ručicu s oprugom, za ormare AC/KC/AT/KT	ASLS2100
Adapter za umetak brave sa tipkom za ormare AC/KC 0	ASLSS1537
Kavezne matice M6 (PAK=10 komada)	ACCNM615
Vijak za maticu M6x16 prema ISO 7380 PAK=10 komada	ACCNK006
Kavezne matice M8 (PAK=10 komada)	ACCNM815
Vijak za maticu M8x16 prema ISO 7380 PAK=10 komada	ACCNK008
Ključ za 5mm "double-bit" bravu WSTL3535 1 komad u isporuci	DV903532