

Tehnički list za artikl: LID14145--

Dina LED 12W 4000K 40° 1100lm, 700mA, IP64, bijele boje

Ceiling-recessed spotlight, dimmable; 02 REC SPOTS FIX LED



Info o proizvodu

12W COB LED recessed spot, IP65, for general application. Suitable for bathroom installation. Requires 700mA constant current driver. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Svjetlosni tok (lm)	1100
Boja svjetla	Hladno bijela
Temperatura boje (K)	4000
Faktor uzvrata boje	≥80
Dimabilno	Ovisi o driveru Da
Klasa zaštite	III
IP stupanj zaštite	IP65
Vrsta svjetiljke	Stropne ugradne svjetiljke
inkl.rasvjetno tijelo	da
Grlo	LED Platine
Kut svjetlosti (°)	40
Efikasnost sustava (lm/W)	91

Tehnički podaci - nastavak

Snaga (W)	12
Pogonski uređaj	Needs to be ordered separately
Pogonska struja mA (mA)	700
Ulazna struja (A)	0,70
Način montaže	Stropna ugradna
Otvor (mm)	Ø 68
Ugradna dubina (mm)	105
Boja	bijela
Materijal	Aluminij tlačni lijev
Visina (mm)	85
Promjer (mm)	83
Dodatni pribor	LID16949--
Potrebni pribor	LID13081--;
ØxV mm	83x85
OTVOR mm	Ø 68

Mjerne skice: Dina LED 12W 4000K 40° 1100lm, 700mA, IP64, bijele boje




Tabela artikla

OPIS	KAT. BROJ
Dina LED 12W 4000K 40° 1100lmm, 700mA, IP64, bijele boje Ceiling-recessed spotlight, dimmable; 02 REC SPOTS FIX LED	LID14145
Potrebni pribor	
LED Driver 700mA, 7-15W, ulaz 220-240V 23 DRIVERS	LID13081
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949