


Tehnički list za artikl: LID14460--

Mercury 4, 7W, 3000K, 450lm, 700mA, 38°, IP44, bijele boje **ECONOMY**

Ceiling-recessed spotlight, dimmable, requires 700mA driver; 02 REC SPOTS FIX LED



Info o proizvodu

6,5W COB LED recessed spot IP65. Requires 700mA driver. Complies with standard EN60598-1 and any other specific standards.



Tehnički podaci

Svjetlosni tok (lm)	550
Boja svjetla	Toplo bijela
Temperatura boje (K)	3000
Faktor uzvrata boje	≥90
Dimabilno	Ovisi o driveru Da
Klasa zaštite	III
IP stupanj zaštite	IP65
Vrsta svjetiljke	Stropne ugradne svjetiljke
inkl.rasvjetno tijelo	da
Grlo	LED Platine

Tehnički podaci - nastavak

Kut svjetlosti (°)	38
Efikasnost sustava (lm/W)	84
Snaga (W)	6,50
Pogonski uređaj	Needs to be ordered separately
Pogonska struja mA (mA)	700
Ulazna struja (A)	0,70
Način montaže	Stropna ugradna
Otvor (mm)	Ø 47
Ugradna dubina (mm)	90
Boja	bijela
Materijal	Aluminij
Visina (mm)	90
Promjer (mm)	53
Dodatni pribor	LID 16949--
Potrebni pribor	LID 15637--; LID 17390--
ØxV mm	53x80
OTVOR mm	Ø 47

Mjerne skice: Mercury 4, 7W, 3000K, 450lm, 700mA, 38°, IP44, bijele boje



Tabela artikla

OPIS	KAT. BROJ
Mercury 4, 7W, 3000K, 450lm, 700mA, 38°, IP44, bijele boje Ceiling-recessed spotlight, dimmable, requires 700mA driver; 02 REC SPOTS FIX LED	LID14460
Potrebni pribor	
LED driver 4 - 8W 230V 700mA IP20 23 DRIVERS	LID15637
LED Driver 6-8W 700ma TRIAC Dimm IP20 230V 23 DRIVERS	LID17390
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949