

Tehnički list za artikl: LID14467--

Flexstrip RGBW, 17, 6w/m, 24vDC, 60LEDs/m, IP20, l=5m

LED Flexstrip, RGB 13,2W/m + WW 4,4W/m, dimmable, 5 meter roll; 08 STRIPS & PROFILES



Info o proizvodu

RGBW flexible LED light strip, with SMD5050 LEDs, 60LEDs/meter, 19,2W/meter. Supplied in 5 meters roll, with white PCB and double adhesive tape for a better fixing. Can be cut every 10cm (6-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Boja svjetla	RGB Toplo bijela
Temperatura boje (K)	RGB+3000
Dimabilno	Ovisi o driveru Da
Klasa zaštite	III
IP stupanj zaštite	IP20
Vrsta svjetiljke	LED traka
Grlo	LED Platine
Kut svjetlosti (°)	120°
Pogonski uređaj	Needs to be ordered separately

Tehnički podaci - nastavak

Radni napon DC (V)	24
Način montaže	Podna Stropna nadgradna Zidna nadgradna
Duljina (mm)	5000
Širina (mm)	12
Visina (mm)	3
Dodatni pribor	LID13862--
(DxŠxV) mm	5000x12x3
Neto duljina (mm)	5.000,00
Neto širina (mm)	12,00
Neto visina (mm)	3,00
Neto masa (kg)	0,24

Tabela artikla

OPIS	KAT. BROJ
Flexstrip RGBW, 17, 6w/m, 24vDC, 60LEDs/m, IP20, l=5m	LID14467
LED Flexstrip, RGB 13,2W/m + WW 4,4W/m, dimmable, 5 meter roll; 08 STRIPS & PROFILES	
Dodatni pribor	
7908/AL, Aluminijski trokutasti profil 2m + PC opalni pokrov	
Suitable for LED Strips 7820, 7821, 7825, 7830, 7831, 7835, 7870, 7875, 7820W, 7830W, 7831W, 7835W; 08 STRIPS & PROFILES	LID13862