


Tehnički list za artikl: LID15113--

Dewy 2 LED 60W 4000K 4800lm 230V IP65 L=1215mm PC/PC sive b.

IK08, vodotijesna, uklj.driver



Krivulja raspodjele svjetla



Info o proizvodu

IP65 LED fitting to replace T8 IP65 traditional waterproof fluorescent. Stainless steel clips included. Polycarbonate body and diffuser. Supplied with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Svjetlosni tok (lm)	6000
Boja svjetla	Neutralno bijela
Temperatura boje (K)	4000
Faktor uzvrata boje	≥80

Tehnički podaci - nastavak

Životni vijek	30.000h
Dimabilno	Ne
Klasa zaštite	I
IP stupanj zaštite	IP65
Otpornost na udarce	IK08
Vrsta svjetiljke	Vodotijesne industrijske svjetiljke
inkl.rasvjetno tijelo	da
Grlo	LED Platine
Efikasnost sustava (lm/W)	100
Faktor snage	0,9
Snaga (W)	60
Pogonski uređaj	LED Driver
Radni napon AC (V)	220-240
Ulazni napon AC (V)	220-240
Pogonska struja mA (mA)	1450
Ulazna struja (A)	1,45
Frekvencija (Hz)	50/60
Način montaže	Stropna nadgradna Zidna nadgradna
Boja	siva
Materijal	PC
Pokrov	Opal
Duljina (mm)	1215
Širina (mm)	113
Visina (mm)	80
Dodatni pribor	LID 16949--
(DxŠxV) mm	1215x113x80

Mjerne skice: Dewy 2 LED 60W 4000K 4800lm 230V IP65 L=1215mm PC/PC sive b.



Tabela artikla

OPIS	KAT. BROJ
Dewy 2 LED 60W 4000K 4800lm 230V IP65 L=1215mm PC/PC sive b. IK08, vodotijesna, uklj.driver	LID15113
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949