

Tehnički list za artikl: LID15776--

Linear BU LED 40/20W 3000K 34°/120° 220-240V IP20 bijele b.

3800lm direkt / 1800lm indirekt



Info o proizvodu

40W UGR17 Linear system with 48 LED spots and 20W uplight for suspended installation, ideal for offices. Complete with 1000mA + 500mA drivers Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Svjetlosni tok (lm)	1800 3800
Boja svjetla	Toplo bijela
Temperatura boje (K)	3000
Faktor uzvrata boje	≥90
Faktor zasjenjivanja	<17
Dimabilno	Ne
Klasa zaštite	I
IP stupanj zaštite	IP20
inkl.rasvjetno tijelo	da
Grlo	LED Platine
Kut svjetlosti (°)	34/120
Snaga sustava (W)	90/95

Tehnički podaci - nastavak

Efikasnost sustava (lm/W)	95 / 90
Faktor snage	0,9
Snaga (W)	40 20
Pogonski uređaj	LED Driver
Radni napon AC (V)	220-240
Pogonska struja mA (mA)	500/1000
Frekvencija (Hz)	50/60
Način montaže	Ovjesna
Dužina ovjesa (mm)	300
Boja	bijela
Materijal	Aluminij
Duljina (mm)	1300
Širina (mm)	70
Visina (mm)	35
Dodatni pribor	LID 15782--
(DxŠxV) mm	1300x70x35

Tabela artikla

OPIS	KAT. BROJ
Linear BU LED 40/20W 3000K 34°/120° 220-240V IP20 bijele b. 3800lm direkt / 1800lm indirekt	LID15776
Dodatni pribor	
Kutnik za Linear A 90° bijele boje Mounting accessory; FOR 38150A/38151A/38150B/38150BU/38150C; 11 OFFICE & KITCHEN	LID15782