

Tehnički list za artikl: LID17282--

Lano Quadro BL M600 40W 3600-4000lm 3-5,7K UGR19 IP20

BACKLIT, uključen 1000mA driver



Info o proizvodu

60x60 adjustable CCT recessed backlit LED panel with microprismatic diffuser for T-rail false ceilings. Uniform lighting, ideal for commercial applications. Complete with 1000mA driver. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Svjetlosni tok (lm)	3600/4000/3800
Boja svjetla	Hladno bijela Neutralno bijela Toplo bijela
Temperatura boje (K)	4000 3000 5700
Faktor uzvrata boje	≥80
Faktor zasjenjivanja	<19
Dimabilno	Ne
Klasa zaštite	II
IP stupanj zaštite	IP20
Vrsta svjetiljke	LED panel

Tehnički podaci - nastavak

inkl.rasvjetno tijelo	da
Grlo	LED Platine
Efikasnost sustava (lm/W)	90
Faktor snage	0,90
Snaga (W)	40
Pogonski uređaj	LED Driver
Radni napon AC (V)	220-240
Ulazni napon AC (V)	220-240
Pogonska struja mA (mA)	1000
Ulazna struja (A)	1
Frekvencija (Hz)	50/60
Način montaže	Stropna ugradna
Ugradna dubina (mm)	60
Boja	bijela
Materijal	Čelik Aluminij
Duljina (mm)	595
Širina (mm)	595
Visina (mm)	30
Dodatni pribor	LID16949--
(DxŠxV) mm	595x595x30

Tabela artikla

OPIS	KAT. BROJ
Lano Quadro BL M600 40W 3600-4000lm 3-5,7K UGR19 IP20 BACKLIT, uključen 1000mA driver	LID17282
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949