

Tehnički list za artikl: LID17787--

Linear BU LED 20-40W 3K/4K/5K CRI90 IP20 UGR17 230V crna

Direkt (20/30/40W) 34° / indirekt (16/20/25W) 120°, kabel 3m



Info o proizvodu

CCT and Power variable 40W UGR17 Linear system with 48 LED spots and uplight for suspended installation, ideal for offices. Complete with 2 x power variable drivers. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Neto duljina (mm)	1.300,00
Neto širina (mm)	35,00
Neto visina (mm)	70,00
Boja	crna
Materijal	Aluminij
Kut svjetlosti (°)	34/120
Faktor zasjenjivanja	<17
Pogonski uređaj	LED Driver
Radni napon AC (V)	220-240
Ulazni napon AC (V)	220-240
Grlo	LED Platine
Efikasnost sustava (lm/W)	95

Tehnički podaci - nastavak

Snaga (W)	40 30 20
Boja svjetla	Hladno bijela Neutralno bijela Toplo bijela
Temperatura boje (K)	5000 4000 3000
Faktor uzvrata boje	≥90
Svjetlosni tok (lm)	max. 1800/3800
Dimabilno	Ne
Klasa zaštite	I
IP stupanj zaštite	IP20
Promjer (mm)	68
(DxŠxV) mm	1300x35x70

Mjerne skice: Linear BU LED 20-40W 3K/4K/5K CRI90 IP20 UGR17 230V crna



OPIS	KAT. BROJ
Linear BU LED 20-40W 3K/4K/5K CRI90 IP20 UGR17 230V crna Direkt (20/30/40W) 34° / indirekt (16/20/25W) 120°, kabel 3m	LID17787