

Tehnički list za artikl: LIG5L03221


Avenida Pole LED 10W 865lm 730 IP66 IK09

1000mm, grafit

rasvjetni stupić, rotosimetrična optika



Krivulja raspodjele svjetla




Tehnički podaci

Neto visina (mm)	1.000,00
Neto promjer (mm)	150,00
Neto masa (kg)	9,70
Min. temperatura okoline (°C)	-40
Maks. temperatura okoline (°C)	50

Tehnički podaci - nastavak

Način montaže	Podna
Boja	grafit
Materijal	Aluminij tlačni ljev
Radni napon AC (V)	220-240
Grlo	LED Platine
Snaga (W)	14
Boja svjetla	Toplo bijela
Temperatura boje (K)	3000
Faktor uzvrata boje	≥70
Svjetlosni tok (lm)	1180
Životni vijek	96.000h / L80 / B10
Dimabilno	Ne
Klasa zaštite	II
IP stupanj zaštite	IP66
inkl.rasvjetno tijelo	da
Promjer (mm)	150
ØxV mm	150x1000
Broj svjetiljki po osiguraču B16	50

Mjerne skice: Avenida Pole LED 10W 865lm 730 IP66 IK09 1000mm, grafit



Avenida Pole LED 10W 865lm 730 IP66 IK09 1000mm, grafit
rasvjetni stupić, rotosimetrična optika

LIG5L03221