




Tehnički list za artikl: LILE0135--

Novia R 600 38/55W 3000/4000K Ra90 UGR19 on/off black

Wall and ceiling light direct/indirect, indirect component can be switched off, adjustable wattage and light color, 38W=5000lm / 55W=7000lm@4000K, 127lm/W@4000K, Ø-600mm H=64/79mm. Articelnumber of the DALI-Module: LILE0136--




Krivulja raspodjele svjetla



Tehnički podaci

Neto visina (mm)	79,00
Neto promjer (mm)	600,00
Neto masa (kg)	6,00
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	40
Način montaže	Zidna nadgradna svjetiljka Stropna nadgradna
Boja	crna RAL 9005
Materijal	PMMA Aluminij
Faktor zasjenjivanja	19
Radni napon AC (V)	220-240
Radni napon DC (V)	216 260 240 186
Efikasnost sustava (lm/W)	127
Snaga (W)	55 38
Boja svjetla	Neutralno bijela Toplo bijela
Temperatura boje (K)	4000 3000
Faktor uzvrata boje	90
Svjetlosni tok (lm)	7000 5000
Životni vijek	50000
Klasa zaštite	I
IP stupanj zaštite	IP20
Energetska klasa	D
Otpornost na udarce	IK06
Promjer (mm)	600
ØxV mm	600x79

Mjerne skice: Nova R 600 38/55W 3000/4000K Ra90 UGR19 on/off black

OPIS

KAT. BROJ

Nova R 600 38/55W 3000/4000K Ra90 UGR19 on/off black

Wall and ceiling light direct/indirect, indirect component can be switched off, adjustable wattage and light color, 38W=5000lm / LILE0135

55W=7000lm@4000K, 127lm/W@4000K, Ø-600mm H=64/79mm. Articelnumber of the DALI-Module: LILE0136--