

Tehnički list za artikl: LIMQ1L605A

M48 Area QU-D 2Modula 96LEDs 4000K IP66 227W 21545lm RAL9006

Version with 2 Modules 96LEDs - SK.II - Power of luminaire 227W with Lumen output 21.545lm @700mA, Power of luminaire 166W with Lumen output 17.225lm @525mA, Power of luminaire 109W with Lumen output 12.425lm @350mA - "Economy" Version (ON-OFF)



Tehnički podaci

Vrsta svjetiljke	Reflektor za industrijske hale
Način montaže	Stropna nadgradna Ovjesna
Boja	RAL 9006 (siva)
Materijal	Aluminij
Pogonski uređaj	LED Driver
Nazivni napon (V)	230
Izvor svjetla	LED
Grlo	LED Platine
Snaga (W)	227
Boja svjetla	Neutralno bijela
Temperatura boje (K)	4000
Vrijednost uzvrata boja	≥70
Svjetlosni tok (lm)	21545

Tehnički podaci - nastavak

Broj svjetiljki	2
Klasa zaštite	II
IP stupanj zaštite	IP66
inkl.rasvjetno tijelo	da
DxŠxV mm	495x340x65

Tabela artikla

OPIS	KAT. BROJ
M48 Area QU-D 2Modula 96LEDs 4000K IP66 227W 21545lm RAL9006	
Version with 2 Modules 96LEDs - SK.II - Power of luminaire 227W with Lumen output 21.545lm @700mA, Power of luminaire 166W with Lumen output 17.225lm @525mA, Power of luminaire 109W with Lumen output 12.425lm @350mA - "Economy" Version (ON-OFF)	LIMQ1L605A
Dodatni pribor	
Stropni nosač za M48 Area RAL9006	LI06MQ900A
Pribor za ovjes za M48, duljina= 1,5m	LI06MQ901J