

Tehnički list za artikl: NLASMU408B

Emergency luminaire ASM WirelessConnect LED 8h 230V AC

Universal mounting, with LiFePO4 battery, exit sign luminaire, with Bluetooth communication.



Tehnički podaci

Neto duljina (mm)	277,00
Neto visina (mm)	184,00
Neto dubina (mm)	46,00
Neto masa (kg)	0,80
Vrsta svjetiljke	Panik svjetiljka
VB-CPS	Sa vlastitom baterijom
Funkcija	WirelessConnect
Izvedba/tip	Metalna zaštita od udara Plosnate svjetiljke
Dizajn	ASM
Boja	srebrna
Piktogram	Slide-in pictogram set (arrow left, right, bottom, top and white foil for single side use) included in accordance with ISO 7010
Područje detekcije (m)	22

Tehnički podaci - nastavak

Vrijeme autonomije (h)	8
Rasvjetno tijelo	LED (2W)
Područje napona (V)	230V AC 50Hz ±20%
Power maintained mode (W)	3,90
Power non-maintained mode (W)	1,50
Power max. (W)	5,30
Baterija (V/Ah)	3,2/3,0 LiFePO4
IP stupanj zaštite	IP40
Udarna čvrstoća	IK03
Način montaže	Zidna nadgradna Stropna nadgradna Univerzalno
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
AA klase E 8101	AA4
Proizvođač	Schrack

Mjerne skice: Emergency luminaire ASM WirelessConnect LED 8h 230V AC

NLASMU...




Tabela artikla

OPIS	KAT. BROJ
Emergency luminaire ASM WirelessConnect LED 8h 230V AC Universal mounting, with LiFePO4 battery, exit sign luminaire, with Bluetooth communication.	NLASMU408B
Dodatni pribor	
Ugradb.okvir za centr.bat.svjetiljku Design KM Required ceiling cut out: 277 x 56 mm	NLKME
Zidni nosač za panik svjetiljke Design KM/KS	NLAWKSU
Accu LiFePO4 3,2V 3,3Ah for LED luminaire For design KM, KSC, KMB, ASM, ZAW, NLIL.L.23., LiFePO4 - Lithium-iron phoshpate battery , UN3480 - UN 3480 : Lithium-Ion batteries, compatible to accu 3,2V 3,3Ah	NLAKKU3233
Cijevni nosač par dužine 500mm bijeli , ožičeni Suitable for design KS, KM, KMB in self contained version with LiFePO4 battery	NL2DWMKS
Zaštitna mrežica za panike KD,KS,LI,M	NLBALL1
Cijevni nosač kromirani, montaža strop	NLDSA000
Ovjesna sajla dužine 2000mm , komplet 1 par	NLCORD2
Ovjesna sajla dužine 4000mm , komplet 1 par	NLCORD4