

Panik svjetiljka KB-DUO ERT-LED 230V, univerz.montaža

In emergency mode switching from LED to ERT-LED for rescue path illumination in 4 directions, modular version with optionally available pictogram panels with viewing distance 14m, 22m, 30m, 520lm





Tehnički podaci

Neto duljina (mm)	326,00
Neto širina (mm)	50,00
Neto visina (mm)	50,00
Neto masa (kg)	1,00
Vrsta svjetiljke	Modularna sigurnosna svjetiljka
VB-CPS	Za centralni panik sustav (CPS)
Funkcija	Sa nadzorom i kombiniranim pogonom
Izvedba/tip	Plastične svjetiljke
Dizajn	KB
Bezhalogena	Plastično kućište, bez halogena
Boja	RAL 9003 (bijela)
Rasvjetno tijelo	ERT-LED (4W) LED (3W)
Lumen	520
Područje napona (V)	230V AC 50Hz ±20%; 230V DC ±20%
Power maintained mode (W)	5,90
Power non-maintained mode (W)	1,10
Power max. (W)	5,90
IP stupanj zaštite	IP65
Udarna čvrstoća	IK05



Tehnički podaci - nastavak

Način montaže	Stropna ugradna opcija
	Zidna nadgradna
	Stropna nadgradna
	Univerzalno
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
AA klase E 8101	AA4
Proizvođač	Schrack

Dimensions (mm)



Drilling distances (mm)



Dimensions (mm) optional pictogram edges

NLKBG



NLKBM



NLKBK



Spacing table - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80

					
2,00	5,85	13,52	14,26	15,07	6,32
2,50	6,57	15,81	16,44	17,16	6,88
3,00	6,51	17,76	18,25	18,99	7,06
3,50	6,65	19,03	19,51	20,06	7,16
4,00	6,40	19,64	20,16	20,66	7,07
5,00	5,98	19,48	20,30	20,96	6,31
6,00	5,50	18,66	19,44	20,31	5,32
7,00	4,51	17,77	18,06	18,55	4,52
8,00	3,55	16,36	16,19	16,06	3,18
9,00	2,67	15,24	14,86	14,47	1,70

Tabela artikla

OPIS	KAT. BROJ
Panik svjetiljka KB-DUO ERT-LED 230V, univerz.montaža	
In emergency mode switching from LED to ERT-LED for rescue path illumination in 4 directions, modular version with optionally available pictogram panels with viewing distance 14m, 22m, 30m, 520lm	NLKBUDUOML
Dodatni pribor	
Piktogramska plexi ploča za lampu KB, komplet. 4 pictograma	NLKBM

Tabela artikla

OPIS	KAT. BROJ
Dodatni pribor	
Piktogramska plexi ploča za lampu KB, komplet. 4 pictograma	NLKBG
Piktogramska plexi ploča za lampu KB, komplet. 4 pictograma	NLKBK
Zaštita od kiše za svjetiljku Design KB od plexiglasa	NLKBRD
Okvir za ugradnju u strop za svjetiljku tip KB Required ceiling cut out: 355 x 70 mm	NLKBE
Kućiste za ugradnju u beton za lampu tip KB	NLKBBE
Paralelni stropni nosač za panik lampu KB	NLAWW008
Par cijevnih nosača 500mm, bijeli, montaža strop	NL2DS
Par cijevnih nosača bijeli, montaža strop	NL2DW
Par cijevnih nosača 500mm, bijeli, montaža strop	NL2PW
Zidni nosač, bijeli, predviđen za: KB,KX,KW,KCD,KE,GX,RX	NLAWX001
Cijevni nosač kromirani, montaža strop	NLDSA000
Ovjesna sjajla dužine 2000mm , komplet 1 par	NLCORD2
Ovjesna sjajla dužine 4000mm , komplet 1 par	NLCORD4