

Tehnički list za artikl: NLMD0100--

Centrala CPS Midicontrol; Punjač 2,5A / max 32 kruga

bez modula NLDCM42MID, bez baterija, s odjeljkom za baterije do 55 Ah, VxŠxD = 1950 x 600 x 450 mm



Tehnički podaci

Neto duljina (mm)	450,00
Neto širina (mm)	600,00
Neto visina (mm)	1.950,00
Neto masa (kg)	105,00

Tabela artikla

OPIS	KAT. BROJ
Centrala CPS Midicontrol; Punjač 2,5A / max 32 kruga bez modula NLDCM42MID, bez baterija, s odjeljkom za baterije do 55 Ah, VxŠxD = 1950 x 600 x 450 mm	NLMD0100
Potrebni pribor	
DCM modul 2kruga za u rack 19" 2x1A For individually centrally switchable emergency luminaires NL..EL, NL...E, max. load 2 x 300VA – fuse 4x F5A, 6,3x32mm. Suitable NLDCM12E for LPS and CPS Micro-, Mini-, Midi-, Maxi- or MultiControl	
DCM modul 2 kruga, pripremni/trajni spoj, 20 lampi /krug, 3A Max. load 2 x 650VA – fuse 4x F5A, 6,3x32mm. Suitable for LPS and CPS Micro-, Mini-, Midi-, Maxi- or MultiControl	NLDCM32
DCM modul 2 kruga, pripremni/tajni spoj, 20 lampi /krug, 4A Max. load 2 x 860VA – fuse 4x F6,3A, 6,3x32mm. Suitable for LPS and CPS Mini-, Midi-, Maxi- or MultiControl	NLDCM42

Tabela artikla

OPIS	KAT. BROJ
Potrebni pribor	
Modul elek.kruga DCM za 19" 2x4A maint./non-maint za Midicon	NLDCM42MID
Max. load 2 x 860VA – fuse 4x F6,3A, 6,3x32mm. Built in into MidiControl at the factory	
Baterije 18kom longlife OGIV 12V/17Ah i kabeli za povezivanje	
Type RPower, incl. cable connectors (NLBAV1728), battery set suitable for 1935W/1h 736W/3h 343W/8h, total weight: 99kg, ventilation requirements according to EN 62485-2: Q=0,79m ³ /h, A=22cm ²	NLBAS017
Baterije 18kom longlife OGIV 12V/26Ah i kabeli za povezivanje	
Type RPower, incl. cable connectors (NLBAV1728), battery set suitable for 2678W/1h 1227W/3h 531W/8h, total weight: 166kg, ventilation requirements according to EN 62485-2: Q=1,2m ³ /h, A=33,5cm ²	NLBAS026
Baterije 18kom longlife OGIV 12V/28Ah i kabeli za povezivanje	
Type RPower, incl. cable connectors (NLBAV1728), battery set suitable for 2575W/1h 1250W/3h 566W/8h, total weight: 164kg, ventilation requirements according to EN 62485-2: Q=1,34m ³ /h, A=37,4cm ²	NLBAS028
Baterije 18kom longlife OGIV 12V/33Ah i kabeli za povezivanje	
Type RPower, incl. cable connectors (NLBAV3375G), battery set suitable for 3421W/1h 1411W/3h 635W/8h, total weight: 198kg, ventilation requirements according to EN 62485-2: Q=1,57m ³ /h, A=44,1cm ²	NLBAS033
Baterije 18kom longlife OGIV 12V/41Ah i kabeli za povezivanje	
Type RPower, type RPower, incl. cable connectors (NLBAV3375-), battery set suitable for 4061W/1h 1630W/3h 719W/8h, total weight: 248kg, ventilation requirements according to EN 62485-2: Q=1,88m ³ /h, A=52,6cm ²	NLBAS040
Baterije 18kom longlife OGIV 12V/44Ah i kabeli za povezivanje	
Type RPower, type RPower, incl. cable connectors (NLBAV3375-), battery set suitable for 4579W/1h 1884W/3h 862W/8h, total weight: 263kg, ventilation requirements according to EN 62485-2: Q=2,15m ³ /h, A=60,1cm ²	NLBAS045
Baterije 18kom longlife OGIV 12V/57Ah i kabeli za povezivanje	
Type RPower, type RPower, incl. cable connectors (NLBAV3375-), battery set suitable for 6324W/1h 2598W/3h 1194W/8h, total weight: 310kg, ventilation requirements according to EN 62485-2: Q=2,83m ³ /h, A=79,2cm ²	NLBAS055
Dodatni pribor	
Plexi vrata za centralu CPS tip Midicontrol	NLPLXMD
Trofazni nadzor napona sa BUS vezom RS485	NLMCLM
Trofazni nadzor napona PC230	NLPC2300
SAM08 query modul 8 nezavisnih ulaza za isk/uklj rasvjete	NLSAM24
Nadzorna ploča sa LCD zaslonom, BUS komunikacija	NLMCT15
Nadzorna ploča sa LCD zaslonom, s ključem, BUS komunikacija	NLMCT15S
With key switch	