

Tehnički list za artikl: NLMN100X17

LPS centrala MiniControl XL, sa baterijama, bez DCM

including batteries, without el. circuit module DCM, max. load: 1500W 1h / 500W 3h / 300W 8h, optionally extendable to max. 32 electrical circuits 640 luminaires, h1500 x w610 x d290mm



Tehnički podaci

Neto širina (mm)	610,00
Neto visina (mm)	1.500,00
Neto dubina (mm)	290,00
Neto masa (kg)	149,00

Tabela artikla

OPIS	KAT. BROJ
LPS centrala MiniControl XL, sa baterijama, bez DCM including batteries, without el. circuit module DCM, max. load: 1500W 1h / 500W 3h / 300W 8h, optionally extendable to max. NLMN100X17 32 electrical circuits 640 luminaires, h1500 x w610 x d290mm	
Potrebni pribor	
DCM modul 2kruga za u rack 19" 2x1A For individually centrally switchable emergency luminaires NL..EL, NL...E, max. load 2 x 300VA – fuse 4x F5A, 6,3x32mm. Suitable NLDCM12E for LPS and CPS Micro-, Mini-, Midi-, Maxi- or MultiControl	
DCM modul 2 kruga, pripremni/trajni spoj, 20 lampi /krug, 3A Max. load 2 x 650VA – fuse 4x F5A, 6,3x32mm. Suitable for LPS and CPS Micro-, Mini-, Midi-, Maxi- or MultiControl	NLDCM32
Dodatni pribor	
E30 PP panel za LPS MiniControlXL MNXL sa ventilatorom Outside dimensions: 1828 x 908 x 434 mm (HxWxD), inside dimensions: 1650 x 730 x 310 mm, colour: RAL7035, protection class NLMNXLE30A II, IP54, 263kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	
Trofazni nadzor napona sa BUS vezom RS485	NLMCLM
Trofazni nadzor napona PC230	NLPC2300
SAM08 query modul 8 nezavisnih ulaza za isk/uklj rasvjete	NLSAM24
Nadzorna ploča sa LCD zaslonom, BUS komunikacija	NLMCT15
Nadzorna ploča sa LCD zaslonom, s ključem, BUS komunikacija With key switch	NLMCT15S