

Tehnički list za artikl: NLMN112A--

Minikontrol centrala 12 krugova, 240 panik/ sigurnosnih svjet.

12 electrical circuits, max. 240 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1h / 500 W 3 h / 300 W 8 h, h x w x d: 1100 x 500 x 230 mm



Tehnički podaci

Neto duljina (mm)	230,00
Neto širina (mm)	500,00
Neto visina (mm)	1.100,00
Neto masa (kg)	140,01

Tabela artikla

OPIS	KAT. BROJ
Minikontrol centrala 12 krugova, 240 panik/sigurnosnih svjet. 12 electrical circuits, max. 240 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1h / 500 W 3 h / 300 W 8 h, h NLMN112A x w x d: 1100 x 500 x 230 mm	
Dodatni pribor	
E30 ormar za panik centrale LPS MN w. fan V=1388 Š=861 D=345 Outside dimensions: 1388 x 861 x 345mm (HxWxD), colour RAL7035, protection class II, IP54, 115kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMNE30
Pleksi vrata za Minikontrol centralu CPS-a	NLPLXMIN
Trofazni nadzor napona sa BUS vezom RS485	NLMCLM
Trofazni nadzor napona PC230	NLPC2300
SAM08 query modul 8 nezavisnih ulaza za isk/uklj rasvjete	NLSAM24
Nadzorna ploča sa LCD zaslonom, BUS komunikacija	NLMCT15
Nadzorna ploča sa LCD zaslonom, s ključem, BUS komunikacija With key switch	NLMCT15S