

Tehnički list za artikl: RPSET4524-

SET:Relaj 24VAC 8A 2CO+PODNOŽJE

Wash tight, PBC relay with marking tag, S-Relay, series RPS



Tehnički podaci

Neto masa (kg)	0,06
Min. temperatura okoline (°C)	-40
Maks. temperatura okoline (°C)	85
Nazivna struja [Omski teret] (A)	8
Nazivni napon [Omski teret]	250VAC
Snaga sklapanja [Omski teret]	2000VA
Maksimalan napon (V)	440VAC/300VDC
Materijal kontakata	AgNi
Početni kontakti otpor (Ohm)	≤100mΩ (1A 6VDC)
Električna izdržljivost (radni ciklus)	50000
Mehanički životni vijek	10000000 Operating cycles
Izolacijski otpor (MΩ*km)	1000MΩ (500VDC)
Početna dielektrična čvrstoća	
Između otvorenih kontakata	1000VAC 1min
Između polova	2500VAC 1min
Između kontakata i svitka	5000VAC 1min
Otpornost na vibracije	10Hz - 150Hz 10g/5g
Vlažnost zraka (%)	5% - 85% RH

Tehnički podaci - nastavak


Podaci o svitku

Napon privlačenja (uklopa) AC (V)	18V
Napon ispada AC	3.6V
Otpor svitka	350 x (1±10%)Ω


Podnožje

Nazivni napon	250V-AC
Nazivna struja (A)	10
Temperaturno područje - Pogon (°C)	-40 to +70
Dielektrična čvrstoća	5000VAC
MOment pritezanja (Nm)	0,6N.m


Dimensions and Circuit Diagram: relay




Dimensions and Circuit Diagram: Socket




Dimensions: Retaining clip




Dimensions: Marking tag




Dijagram: SET:Releј 24VAC 8A 2CO+PODNOŽJE



Electrical endurance 1) Operations 2) Breaking capacity



Coil operating range 1) Coil voltage 2) Ambient temperature 3) Recommended voltage



OPIS

KAT. BROJ

SET:Releji 24VAC 8A 2CO+PODNOŽJE

Wash tight, PBC relay with marking tag, S-Relay, series RPS

RPSET4524