

Tehnički list za artikl: SR3PDIEM01

PDU Essential Metered; 8xC13; 230V; 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/230V | 3,6kW
- Output: 8xC13 0° IEC Socket
- Supply cable: 2.0m | 1.5mm²
- with CEE7/7 angled plug
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Tehnički podaci

Neto duljina (mm)	437,40
Neto širina (mm)	45,00

Tehnički podaci - nastavak

Neto visina (mm)	60,00
Neto masa (kg)	1,10
EAN	4057298233012
CIJENA	1.516,00
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	45
Nazivni napon	230V
IP stupanj zaštite	IP20
Tip proizvoda	Metered Essential
Broj utičnica	8
Outlet type	8xC13
Nazivna struja (A)	16
Phases per feed	1
Tip priključka	CEE 7/7 (Type E/F)
Protokol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Način ugradnje	Bracket (L-shape)

OPIS	KAT. BROJ
PDU Essential Metered; 8xC13; 230V; 16A	SR3PDIEM01
Measurement per phase, incl. mounting bracket with screws	