

Tehnički list za artikl: SR3PDIEM09

# PDU Essential Metered; 24xC13; 6xC19; 400V; 32A

Measurement per phase, incl. mounting bracket with screws



## SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 32A/400V | 22kW
- Output: 24xC13 0° IEC Socket 6xC19 90° IEC Socket
- 6xMiniature Circuit Breaker C16A
- split into three phases, each phase split into two blocks, each block fused with a MCB
- Supply cable: 3.0m | 4mm<sup>2</sup>
- with CEE 32A plug, red
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

## Tehnički podaci

|                                |                                                                                                                                  |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Neto duljina (mm)              | 1.756,08                                                                                                                         |
| Neto širina (mm)               | 45,00                                                                                                                            |
| Neto visina (mm)               | 94,00                                                                                                                            |
| Neto masa (kg)                 | 5,40                                                                                                                             |
| EAN                            | 4057298233111                                                                                                                    |
| CIJENA                         | 2.844,00                                                                                                                         |
| Min. temperatura okoline (°C)  | -5                                                                                                                               |
| Maks. temperatura okoline (°C) | 45                                                                                                                               |
| Nazivni napon                  | 400V                                                                                                                             |
| IP stupanj zaštite             | IP20                                                                                                                             |
| Tip proizvoda                  | Metered Essential                                                                                                                |
| Broj utičnica                  | 30                                                                                                                               |
| Outlet type                    | 24 x IEC320 C13 und 6 x IEC320 C19                                                                                               |
| Nazivna struja (A)             | 32                                                                                                                               |
| Phases per feed                | 3                                                                                                                                |
| Tip priključka                 | CEE 32 A red                                                                                                                     |
| Protokol                       | CLI<br>IPv6<br>IPv4<br>DNS<br>SMTPS<br>SSH<br>HTTP<br>NTP<br>DHCP<br>SMTP<br>HTTPS<br>SNMP Trap<br>Syslog<br>SNMPv2/v3<br>Telnet |
| Način ugradnje                 | Bracket (L-shape)                                                                                                                |

| OPIS                                                      | KAT. BROJ  |
|-----------------------------------------------------------|------------|
| PDU Essential Metered; 24xC13; 6xC19; 400V; 32A           |            |
| Measurement per phase, incl. mounting bracket with screws | SR3PDIEM09 |