

Tehnički list za artikl: SR3PDIEM11

PDU Essential Metered; 36xC13; 6xC19; 400V; 32A

Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 32A/400V | 22kW
- Output: 36xC13 0° IEC Socket 6xC19 90° IEC Socket
- 6xMiniature Circuit Breaker C16A
- split into three phases, each phase split into two blocks, each block fused with a MCB
- Supply cable: 3.0m | 4mm²
- with CEE 32A plug, red
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Tehnički podaci

Neto duljina (mm)	2.011,08
Neto širina (mm)	45,00
Neto visina (mm)	94,00
Neto masa (kg)	5,30
EAN	4057298233135
CIJENA	2.954,00
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	45
Nazivni napon	400V
IP stupanj zaštite	IP20
Tip proizvoda	Metered Essential
Broj utičnica	42
Outlet type	36 x IEC320 C13 und 6 x IEC320 C19
Nazivna struja (A)	32
Phases per feed	3
Tip priključka	CEE 32 A red
Protokol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Način ugradnje	Bracket (L-shape)

OPIS	KAT. BROJ
PDU Essential Metered; 36xC13; 6xC19; 400V; 32A Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!	SR3PDIEM11