

Tehnički list za artikl: SR3PDIPM01

Napojna letva PRO metered, 16xC13, 4xC19, 230V, 16A

Mjerenje po fazi, uklj. montažni nosač s vijcima



SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 16 A / 230 V | 3,6 kW
- Supply cable: 3,0 m | 2,5 mm²
- mit CEE plug 16 A blue
- Output: 16 x C13 IEC Socket + 4 x C19 IEC Socket
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)
- Packed in cardboard box
- Length 1076 mm

Tehnički podaci

Neto duljina (mm)	1.076,00
Neto širina (mm)	56,00
Neto visina (mm)	70,00
Neto masa (kg)	3,00
EAN	4057298202872
CIJENA	3.012,00
Min. temperatura okoline (°C)	0
Maks. temperatura okoline (°C)	50
Nazivni napon	230V
IP stupanj zaštite	IP20
Tip proizvoda	Metered
Broj utičnica	20
Outlet type	16 x IEC320 C13 und 4 x IEC320 C19
Nazivna struja (A)	16
Phases per feed	1
Tip priključka	CEE 16 A blue
Protokol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Način ugradnje	Bracket (L-shape)

OPIS	KAT. BROJ
Napojna letva PRO metered, 16xC13, 4xC19, 230V, 16A	SR3PDIPM01
Mjerenje po fazi, uklj. montažni nosač s vijcima	