

Tehnički list za artikl: SR3PDIPP01

PDU PRO Metered+, 24xCombo Outlets (C13, C15, C19, C21), 230V, 16A

Mjerenje po utičnici, uklj. montažni nosač s vijcima



SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 16 A / 230 V | 3.6 kW
- Input: 3.0 m | 2.5 mm²
- with CEE plug 16 A blue
- Output: 24x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </I

Tehnički podaci

Neto duljina (mm)	1.191,00
Neto širina (mm)	56,00
Neto visina (mm)	71,00
EAN	4057298230257
CIJENA	5.532,00
Min. temperatura okoline (°C)	0
Maks. temperatura okoline (°C)	50
Nazivni napon	230V
IP stupanj zaštite	IP20
Tip proizvoda	Metered+
Broj utičnica	24
Outlet type	24 x Combo Socket (C13/C15/C19/C21)
Nazivna struja (A)	16
Phases per feed	1
Tip priključka	CEE 16 A blue
Protokol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Način ugradnje	Bracket (L-shape)

OPIS	KAT. BROJ
PDU PRO Metered+, 24xCombo Outlets (C13, C15, C19, C21), 230V, 16A	SR3PDIPP01
Mjerenje po utičnici, uklj. montažni nosač s vijcima	