

Tehnički list za artikl: SR3PDIPS09

# PDU PRO Switched, 36xCombo (C13,C15,C19,C21), 400V, 32A, RCM

Mjerenje po fazi, (mjerenje po utičnici može se dobiti nadogradnjom licence), nadzor diferencijalne struje po fazi, uklapanje po utičnici, uklj. montažni nosač s vijcima



## SCHRACK-Info

- PDU PRO Switched RCM
- Metering per phase
- Can be upgraded to measuring per socket at any time via licence (SR3PAB0011,SR3PAB0012,SR3PAB0013)
- Residual Current Monitoring per phase, Typ B
- switchable sockets
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm<sup>2</sup>
- with CEE plug 32 A red
- Ausgang: 36x Combo C13/C15/C19/C21
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)

- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) &lt;/l

## Tehnički podaci

|                                |                                                                                                                                                        |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Neto duljina (mm)              | 2.078,10                                                                                                                                               |
| Neto širina (mm)               | 56,00                                                                                                                                                  |
| Neto visina (mm)               | 71,00                                                                                                                                                  |
| EAN                            | 4057298230622                                                                                                                                          |
| CIJENA                         | 9.726,00                                                                                                                                               |
| Min. temperatura okoline (°C)  | 0                                                                                                                                                      |
| Maks. temperatura okoline (°C) | 50                                                                                                                                                     |
| Nazivni napon                  | 400V                                                                                                                                                   |
| IP stupanj zaštite             | IP20                                                                                                                                                   |
| Tip proizvoda                  | Switched                                                                                                                                               |
| Broj utičnica                  | 36                                                                                                                                                     |
| Outlet type                    | 36 x Combo Socket (C13/C15/C19/C21)                                                                                                                    |
| Nazivna struja (A)             | 32                                                                                                                                                     |
| Phases per feed                | 3                                                                                                                                                      |
| Tip priključka                 | CEE 32 A red                                                                                                                                           |
| Protokol                       | LDAP<br>IPv6<br>IPv4<br>DNS<br>SNMPv1<br>SSH<br>HTTP<br>SNMPv3<br>SNMPv2<br>NTP<br>SSH2<br>DHCP<br>ModBus /TCP<br>SMTP<br>HTTPS<br>SNMP Trap<br>Syslog |
| Način ugradnje                 | Bracket (L-shape)                                                                                                                                      |

PDU PRO Switched, 36xCombo (C13,C15,C19,C21), 400V, 32A, RCM

Mjerenje po fazi, (mjerenje po utičnici može se dobiti nadogradnjom licence), nadzor diferencijalne struje po fazi, uklapanje po utičnici, uklj. montažni nosač s vijcima

SR3PDIPS09