

Tehnički list za artikl: XC1608911 -

DIGI-SAT 3000 koaks.75Ohm 1.0/6.6, 95dB, kl.A, LS0H, Eca, 100m

dvostruki omotač, kolut 100m



SCHRACK info

To guarantee high-quality, noise-free transmission of the high frequencies (from approx. 950 to 2150 MHz) from the LNB via multiswitch and SAT wall outlet to the SAT receiver it is necessary to use high-grade coax cables. Our high-frequency cables owe their top quality to their top-of-the-line components, cutting-edge production technology and the number of their shielding layers.



Tehnički podaci

Klasa	Klasa A
Unutarnji vodič	1,02 CCS
Promjer izolacije	4,60 Cell PE
Vanjski vodič	Aluminijska poliesterska folija
Splet	0,12 Al x 16 x 7
Pokrov spleta (%)	75
Dimenzije zaslona (dB)	95
Promjer (mm)	6,60
Vanjski omotač kabela	LS0H

Tehnički podaci - nastavak

Euro-norma prema EN50575	Eca
Boja plašta	bijela
Min. radijus savijanja (mm)	60
Nominalna težina (kg/km)	45
Otpor (Ohm)	75 ± 3
Istosmjerni otpor pri 20° C (Ohm/100m)	2,20
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	70
Duljina/pakiranje	100m - špula
Kapacitet	52 ± 4 pF/m
Neto duljina (mm)	1.000,00
Neto promjer (mm)	6,60
Neto masa (kg)	0,05

TIPIČNE VRIJEDNOSTI

Nominalno prigušenje:	
50 MHz	3.30dB / 100m
100 MHz	5.40dB / 100m
200 MHz	7.90dB / 100m
300 MHz	9.70dB / 100m
470 MHz	12.70dB / 100m
860 MHz	18.30dB / 100m
1000 MHz	20.20dB / 100m
1350 MHz	24.10dB / 100m
1750 MHz	28.60dB / 100m
2050 MHz	30.50dB / 100m
2250 MHz	32.10dB / 100m
2400 MHz	33.30dB / 100m
Gubici zbog povratnog signala:	
5 - 1.000 MHz	more than 30dB
1.000 - 2.000 MHz	more than 24dB
2.000 - 3.000 MHz	more than 20dB

Tabela artikla

OPIS	KAT. BROJ
DIGI-SAT 3000 koaks.75Ohm 1.0/6.6,95dB,kl.A,LSOH,Eca,100m dvostruki omotač, kolut 100m	XC1608911
Dodatni pribor	
SAT koaksijalni F-utikač, natisni za DIGI-SAT 3000, 3030, 3040, 3050	XC16004983
SAT koaksijalni alat za kompresiju F-utikača XC1600xxxx .	XC1600720
DIGI-SAT alat za skidanje izolac. koaks. kab. 6.6-6.8 i 11 mm .	XC1600710
SAT završna utičnica R/TV/SAT, klasa A, RAL9010 uključen okvir 80x80mm i N/Ž kućište, RAL9010	HSATD3M
SAT utič. kraj. 4x,radio/CATV/2xSAT,kl.A,okvir 80x80,9010 uključen okvir 80x80mm i N/Ž kućište, RAL9010	HSATD4M
Utičnica završna 2-struka, 2dB,kl.A,okvir+kućište,RAL9010 uključen okvir 80x80mm i N/Ž kućište, RAL9010	HSBKD2M